

Double actuator pushbutton



Part no. M22-T-DD
216396
EL Number 4355415
(Norway)

General specifications	
Product name	Eaton Moeller® series M22 Accessory Double actuator pushbutton
Part no.	M22-T-DD
EAN	4015082163969
Product Length/Depth	33 millimetre
Product height	23 millimetre
Product width	58 millimetre
Product weight	0.008 kilogram
Compliances	Contact Manufacturer
Certifications	CE
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Double actuator pushbutton
Catalog Notes	Do not use in conjunction with M22S-ST legend plate mount, since degree of protection cannot be guaranteed Silicone transparent version for harsh environmental conditions and application in the food industry
Features & Functions	
Color	Colorless
Features	Transparent
Material	Silicone
Shape	Round
General information	
Degree of protection	NEMA 13 NEMA 12 NEMA 3R NEMA 4X
Model	Other
Protection	Additional protection for double actuator pushbuttons
Used with	Double actuator pushbuttons
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Communication	
Connection to SmartWire-DT	No
Contacts	
Force for positive opening - min	0 N
Design verification	
Equipment heat dissipation, current-dependent P _{vid}	0 W
Heat dissipation capacity P _{diss}	0 W
Heat dissipation per pole, current-dependent P _{vid}	0 W
Rated operational current for specified heat dissipation (I _n)	0 A
Static heat dissipation, non-current-dependent P _{vs}	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Protective cap for command devices (EC002040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Protective cover for command devices (ecl@ss13-27-37-12-07 [ACO047016])			
Colour			Colourless
Transparent			Yes
Shape			Round
Model			Other