## Shroud for unused terminal, Protection against direct contact., For covering unused terminals on three-phase busbar link B3...-PKZ4



Part no. H-B3-PKZ4 220228

eneral specifications	5 . M. W. O. J. ENTER. S
Product name	Eaton Moeller® series PKZ4 Accessory Shroud for unused terminal
Part no.	H-B3-PKZ4
EAN	4015082202286
Product Length/Depth	40 millimetre
Product height	9 millimetre
Product width	35 millimetre
Product weight	0.005 kilogram
Certifications	CSA Class No.: 3211-06 UL File No.: E36332 UL CSA File No.: 165628 UL 508 CE CSA-C22.2 No. 14 UL Category Control No.: NLRV CSA IEC/EN 60947-4-1 UL CSA
Product Tradename	PKZ4
Product Type	Accessory
Product Sub Type	Shroud for unused terminal
eatures & Functions	
Functions	For covering unused terminals on three-phase commoning link B3PKZ4
eneral information	
Accessory/spare part type	Cover
Product category	Accessories
Protection	Protection against direct contact
limatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
esign verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid  Retad operational current for specified heat dissipation (In)	0 W 0 A
Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current dependent Pro-	
Static heat dissipation, non-current-dependent Pvs	0 W  Meets the product standard's requirements
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])

Type of accessory/spare part	Cover
Accessory	Yes
Spare part	No