Series element, 12-240VAC/DC, for LED 12-30V



Part no. M22-XLED-T 231079

EL Number 4355449

(Norway)

General specifications	
Product name	Eaton Moeller® series M22 Accessory LED
Part no.	M22-XLED-T
EAN	4015082310790
Product Length/Depth	37 millimetre
Product height	30 millimetre
Product width	10 millimetre
Product weight	0.011 kilogram
Compliances	CE Marked
Certifications	CSA Std. C22.2 No. 94-91 UL 508 IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 IEC/EN 60947-5 CSA-C22.2 No. 94-91 UL UL Category Control No.: NKCR UL File No.: E29184 CSA CSA CSA Class No.: 3211-03 CSA File No.: 012528 CSA-C22.2 No. 14-05 CE
Product Tradename	M22
Product Type	Accessory
Product Sub Type	LED
Catalog Notes	LED test elements
Features & Functions	
Functions	For de-coupled function test (lamp test)
General information	
Accessory/spare part type	Accessory
Degree of protection	IP20
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	80 °C
Electrical rating	
Rated operational voltage	12 - 240 V AC/DC
Communication	
Connection to SmartWire-DT	No
Contacts	
Force for positive opening - min	0 N
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0.1 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device (accessories) (ecl@ss13-27-37-12-92 [AC0037015])

Type of electrical accessory/spare part	Resistor block
Type of mechanical accessory/spare part	Other
Accessory	Yes
Spare part	No