

Potentiometer, Classical, M22, 22.5 mm, R 10 k $\Omega$ , P 0.5 W, Bezel: black

Part no. **M22S-R10K**  
**232233**  
 EL Number **4355471**  
 (Norway)

General specifications		
Product name		Eaton Moeller® series M22 Potentiometer
Part no.		M22S-R10K
EAN		4015082322335
Product Length/Depth		70 millimetre
Product height		29 millimetre
Product width		29 millimetre
Product weight		0.034 kilogram
Compliances		RoHS Compliant
Certifications		CSA Class No.: 3211-03 UL CSA-22.2 No. 14-05 CE IEC/EN 60947-5-1 IEC/EN 60947 UL Category Control No.: NKCR VDE 0660 UL 508 UL File No.: E29184 CSA File No.: 012528 CSA
Product Tradename		M22
Product Type		Potentiometer
Product Sub Type		None
Features & Functions		
Bezel color		Black
Design		Classical
Electric connection type		Screw connection
Fitted with:		3 individual screw terminals
General information		
Accuracy		$\pm 10\%$ (linear), Resistance value
Degree of protection		IP66 NEMA Other
Lifespan, mechanical		25,000 Operations
Opening diameter		22.5 mm
Overvoltage category		III
Pollution degree		3
Rated impulse withstand voltage (Uimp)		4000 V AC
Type		Potentiometer
Used with		Modular pushbutton
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		
Terminal capacity (solid)		0.5 - 1.5 mm <sup>2</sup>
Terminal capacity (stranded)		0.5 - 1.5 mm <sup>2</sup>
Tightening torque		0.5 Nm, Screw terminals

<b>Electrical rating</b>		
Power consumption		0.5 W
Rated insulation voltage (Ui)		250 V
Rated power		0.5 V-A
Resistance		10000 Ohm
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.5 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Potentiometer for command devices (EC001027)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Potentiometer for command devices (ecl@ss13-27-37-12-27 [AKF045019])			
Resistance		Ohm	10000
Power consumption		W	0.5
Hole diameter		mm	22.5
Number of revolutions			1 - 1
Type of electric connection			Screw connection
Degree of protection (IP)			IP66
Degree of protection (NEMA)			Other