

Undervoltage release, 400 V, non-delayed, 1HP

Part no. **Z-USA/400**
248290

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-USA/400
EAN		4015082482909
Product Length/Depth		80 millimetre
Product height		65.5 millimetre
Product width		17.5 millimetre
Product weight		0.104 kilogram
Compliances		RoHS conform
Certifications		EN45545-2 IEC 61373
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Undervoltage release
Additional equipment required		Under voltage coil
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1
Device fitting		Universal
Functions		Under voltage coil
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		400 V
Rated switch current		0 A
Suitable for current of main contact unit - max		0 A
Tripping time		Non-delayed
Type		Accessory Accessory for miniature circuit breaker
Used with		Undervoltage releases Accessory for miniature circuit breaker Accessory
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Universal
Function		Under voltage coil
Width in number of modular spacings		1
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1

Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0
Rated voltage	V	400
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0