

Shunt release, up to 125A, 110-415V, 1.5HP

**Part no.** Z-LHASA/230  
**248442**  
**EL Number** 1609566  
**(Norway)**

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-LHASA/230
EAN		4015082484422
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		39.1 millimetre
Product weight		0.158 kilogram
Compliances		RoHS conform
Certifications		IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Shunt release
Additional equipment required		Shunt release (for power circuit breaker)
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1.5
Device fitting		Miniature circuit breaker (MCB)
EL number		1609566
Functions		Shunt release (for power circuit breaker)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		230 V
Rated switch current		2 A
Suitable for current of main contact unit - max		2 A
Type		Accessory Accessory for miniature circuit breaker
Used with		Shunt releases
Voltage type		AC

## Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Miniature circuit breaker (MCB)
Function		Shunt release (for power circuit breaker)
Width in number of modular spacings		1.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1

Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	2
Rated voltage	V	230
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	2