

Circuit-breaker, 3p, 200A

Part no. **NZMN2-S200**
265741

General specifications	
Product name	Eaton Moeller series NZM molded case circuit breaker magnetic
Part no.	NZMN2-S200
EAN	4015082657413
Product Length/Depth	149 millimetre
Product height	184 millimetre
Product width	105 millimetre
Product weight	2.332 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 60947 IEC
Product Tradename	NZM
Product Type	Molded case circuit breaker
Product Sub Type	Magnetic
Delivery program	
Application	Use in unearthed supply systems at 690 V
Type	Circuit breaker
Circuit breaker frame type	NZM2
Number of poles	Three-pole
Amperage Rating	200 A
Release system	Thermomagnetic release
Special features	Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) Motor protection in conjunction with overload relay With short-circuit release Without overload release I _r IEC/EN 60947-4-1, IEC/EN 60947-2 The circuit-breaker fulfills all requirements for AC-3 switching category. Rated current = rated uninterrupted current: 200 A
Technical Data - Electrical	
Voltage rating	690 V - 690 V
Rated insulation voltage (U _i)	1000 V
Rated impulse withstand voltage (U _{imp}) at auxiliary contacts	6000 V
Rated impulse withstand voltage (U _{imp}) at main contacts	8000 V
Rated operational current	196 A (400 V AC-3)
Rated short-time withstand current (t = 0.3 s)	1.9 kA
Rated short-time withstand current (t = 1 s)	1.9 kA
Instantaneous current setting (I _i) - min	8 A
Instantaneous current setting (I _i) - max	44328 A
Overload current setting (I _r) - min	0 A
Overload current setting (I _r) - max	0 A
Short-circuit release non-delayed setting - min	1600 A
Short-circuit release non-delayed setting - max	2500 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz	85 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz	35 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 440 V, 50/60 Hz	35 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 525 V, 50/60 Hz	25 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 690 V, 50/60 Hz	5 kA
Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz	187 kA
Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz	105 kA
Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz	74 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz		53 kA
Rated short-circuit making capacity Icm at 690 V, 50/60 Hz		40 kA
Rated operating power at AC-3, 230 V		55 kW
Rated operating power at AC-3, 400 V		110 kW
Short-circuit total breaktime		< 10 ms
Electrical connection type of main circuit		Screw connection
Isolation		300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max		120
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		10000 operations at 400 V AC-1 5000 operations at 690 V AC-3 6500 operations at 400 V AC-3 7500 operations at 690 V AC-1 6500 operations at 415 V AC-3 10000 operations at 415 V AC-1
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		Built-in device fixed built-in technique Fixed
Degree of protection		IP20 IP20 (basic degree of protection, in the operating controls area)
Degree of protection (IP), front side		IP40 (with insulating surround) IP66 (with door coupling rotary handle)
Degree of protection (terminations)		IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
Protection against direct contact		Finger and back-of-hand proof to VDE 0106 part 100
Shock resistance		20 g (half-sinusoidal shock 20 ms)
Switch off technique		Magnetic
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn) Motor protection in conjunction with overload relay With short-circuit release Without overload release Ir IEC/EN 60947-4-1, IEC/EN 60947-2 The circuit-breaker fulfills all requirements for AC-3 switching category. Rated current = rated uninterrupted current: 200 A
Lifespan, mechanical		20000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Screw terminal
Optional terminals		Box terminal. Connection on rear. Tunnel terminal
Terminal capacity (control cable)		0.75 mm ² - 1.5 mm ² (2x) 0.75 mm ² - 2.5 mm ² (1x)
Terminal capacity (aluminum solid conductor/cable)		16 mm ² (1x) at tunnel terminal 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 10 mm ² - 16 mm ² (2x) direct at switch rear-side connection
Terminal capacity (aluminum stranded conductor/cable)		25 mm ² - 50 mm ² (2x) direct at switch rear-side connection 25 mm ² - 50 mm ² (1x) direct at switch rear-side connection 25 mm ² - 185 mm ² (1x) at tunnel terminal
Terminal capacity (copper busbar)		Max. 24 mm x 8 mm direct at switch rear-side connection Min. 16 mm x 5 mm direct at switch rear-side connection M8 at rear-side screw connection
Terminal capacity (copper solid conductor/cable)		6 mm ² - 16 mm ² (2x) direct at switch rear-side connection 10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 10 mm ² - 16 mm ² (1x) at box terminal 6 mm ² - 16 mm ² (2x) at box terminal 16 mm ² (1x) at tunnel terminal
Terminal capacity (copper stranded conductor/cable)		25 mm ² - 70 mm ² (2x) at box terminal 25 mm ² - 185 mm ² (1x) at box terminal 25 mm ² - 185 mm ² (1x) direct at switch rear-side connection 25 mm ² - 70 mm ² (2x) direct at switch rear-side connection 25 mm ² - 185 mm ² (1x) at 1-hole tunnel terminal
Terminal capacity (copper strip)		Max. 10 segments of 16 mm x 0.8 mm at box terminal Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched)

		Max. 8 segments of 24 mm x 1 mm (2x) at box terminal Min. 2 segments of 9 mm x 0.8 mm at box terminal Max. 10 segments of 24 mm x 0.8 mm at rear-side connection (punched)
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		200 A
Equipment heat dissipation, current-dependent		48 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		Short-circuit protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss13-27-37-04-01 [AG2529021])		
Overload release current setting	A	0 - 0
Adjustment range undelayed short-circuit release	A	8 - 44328
With thermal overload protection		No
Phase failure sensitive		No
Switch off technique		Magnetic
Rated operating voltage	V	690 - 690
Rated permanent current Iu	A	200
Rated operation power at AC-3, 230 V	kW	55
Rated operation power at AC-3, 400 V	kW	110
Power loss	W	38
Type of electrical connection of main circuit		Screw connection
Type of control element		Rocker lever
Device construction		Built-in device fixed built-in technique
With integrated auxiliary switch		No
With integrated under voltage release		No

Number of poles		3
Rated short-circuit breaking capacity I _{cu} at 400 V, AC	kA	35
Degree of protection (IP)		IP20
Height	mm	184
Width	mm	105
Depth	mm	149