

## Circuit-breaker, 3p, 50A

**Part no.**                    **NZMC1-A50**  
**271393**

| <b>General specifications</b>   |  |
|---|--|
| Product name  | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic   |
| Part no.  | NZMC1-A50  |
| EAN   | 4015082713935  |
| Product Length/Depth  | 88 millimetre  |
| Product height  | 145 millimetre   |
| Product width   | 90 millimetre  |
| Product weight  | 1.05 kilogram  |
| Compliances   | RoHS conform   |
| Certifications  | IEC<br>IEC/EN 60947  |
| Product Tradename   | NZM  |
| Product Type  | Molded case circuit breaker  |
| Product Sub Type  | Thermo-magnetic  |
| <b>Delivery program</b>   |  |
| Application   | Use in unearthed supply systems at 690 V   |
| Type  | Circuit breaker  |
| Circuit breaker frame type  | NZM1   |
| Number of poles   | Three-pole   |
| Amperage Rating   | 50 A   |
| Release system  | Thermomagnetic release   |
| Features  | Protection unit  |
| Special features  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I <sub>cn</sub> )<br>Rated current = rated uninterrupted current: 50 A<br>Terminal capacity hint: Up to 95 mm <sup>2</sup> can be connected depending on the cable manufacturer. |
| <b>Technical Data - Electrical</b>  |  |
| Voltage rating  | 690 V - 690 V  |
| Rated insulation voltage (U <sub>i</sub> )  | 690 V AC   |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at auxiliary contacts                   | 6000 V   |
| Rated impulse withstand voltage (U <sub>imp</sub> ) at main contacts                        | 6000 V   |
| Instantaneous current setting (I <sub>i</sub> ) - min                                       | 300 A  |
| Instantaneous current setting (I <sub>i</sub> ) - max                                       | 500 A  |
| Overload current setting (I <sub>r</sub> ) - min  | 40 A   |
| Overload current setting (I <sub>r</sub> ) - max  | 50 A   |
| Short delay current setting (I <sub>sd</sub> ) - min  | 0 A  |
| Short delay current setting (I <sub>sd</sub> ) - max  | 0 A  |
| Short-circuit release non-delayed setting - min   | 300 A  |
| Short-circuit release non-delayed setting - max   | 500 A  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz     | 55 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz | 36 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz     | 22.5 kA  |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 525 V, 50/60 Hz     | 6 kA   |
| Rated short-circuit breaking capacity I <sub>cs</sub> (IEC/EN 60947) at 690 V, 50/60 Hz     | 6 kA   |
| Rated short-circuit making capacity I <sub>cm</sub> at 240 V, 50/60 Hz                      | 121 kA   |
| Rated short-circuit making capacity I <sub>cm</sub> at 400/415 V, 50/60 Hz                  | 76 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 440 V, 50/60 Hz                      | 63 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 525 V, 50/60 Hz                      | 24 kA  |
| Rated short-circuit making capacity I <sub>cm</sub> at 690 V, 50/60 Hz                      | 14 kA  |

|   |  |  |
|---|--|--|
| Short-circuit total breaktime                                   |  | < 10 ms  |
| Electrical connection type of main circuit                      |  | Frame clamp  |
| Isolation   |  | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts)   |
| Number of operations per hour - max                             |  | 120  |
| Handle type   |  | Rocker lever   |
| Utilization category  |  | A (IEC/EN 60947-2)   |
| Overvoltage category  |  | III  |
| Pollution degree  |  | 3  |
| Lifespan, electrical  |  | 10000 operations at 415 V AC-1<br>10000 operations at 400 V AC-1<br>5000 operations at 690 V AC-1  |
| Direction of incoming supply                                    |  | As required  |
| <b>Technical Data - Mechanical</b>                              |  |  |
| Mounting Method   |  | DIN rail (top hat rail) mounting optional<br>Built-in device fixed built-in technique<br>Fixed   |
| Degree of protection  |  | IP20<br>IP20 (basic degree of protection, in the operating controls area)  |
| Degree of protection (IP), front side                           |  | IP66 (with door coupling rotary handle)<br>IP40 (with insulating surround)   |
| Degree of protection (terminations)                             |  | IP10 (tunnel terminal)<br>IP00 (terminations, phase isolator and strip terminal)   |
| Protection against direct contact                               |  | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110  |
| Shock resistance  |  | 20 g (half-sinusoidal shock 20 ms)   |
| Number of auxiliary contacts (change-over contacts)             |  | 0  |
| Number of auxiliary contacts (normally closed contacts)         |  | 0  |
| Number of auxiliary contacts (normally open contacts)           |  | 0  |
| Position of connection for main current circuit                 |  | Front side   |
| Climatic proofing   |  | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30   |
| Special features  |  | Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)<br>Rated current = rated uninterrupted current: 50 A<br>Terminal capacity hint: Up to 95 mm <sup>2</sup> can be connected depending on the cable manufacturer.    |
| Lifespan, mechanical  |  | 20000 operations   |
| <b>Technical Data - Mechanical - Terminals</b>                  |  |  |
| Standard terminals  |  | Box terminal   |
| Optional terminals  |  | Connection on rear. Screw terminal. Tunnel terminal  |
| Terminal capacity (control cable)                               |  | 0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)<br>0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)   |
| Terminal capacity (aluminum solid conductor/cable)              |  | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>16 mm <sup>2</sup> (1x) at tunnel terminal<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection   |
| Terminal capacity (aluminum stranded conductor/cable)           |  | 25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at tunnel terminal<br>25 mm <sup>2</sup> - 35 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 35 mm <sup>2</sup> (2x) direct at switch rear-side connection  |
| Terminal capacity (copper busbar)                               |  | Min. 12 mm x 5 mm direct at switch rear-side connection<br>M6 at rear-side screw connection<br>Max. 16 mm x 5 mm direct at switch rear-side connection   |
| Terminal capacity (copper solid conductor/cable)                |  | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) at box terminal<br>6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) at box terminal<br>16 mm <sup>2</sup> (1x) at tunnel terminal         |
| Terminal capacity (copper stranded conductor/cable)             |  | 25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at 1-hole tunnel terminal<br>6 mm <sup>2</sup> - 25 mm <sup>2</sup> (2x) at box terminal<br>25 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) at box terminal<br>10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) direct at switch rear-side connection |
| Terminal capacity (copper strip)                                |  | Max. 9 segments of 9 mm x 0.8 mm at box terminal<br>Min. 2 segments of 9 mm x 0.8 mm at box terminal   |
| <b>Design verification as per IEC/EN 61439 - technical data</b> |  |  |
| Rated operational current for specified heat dissipation (In)   |  | 50 A   |
| Equipment heat dissipation, current-dependent                   |  | 13.2 W   |

|  |  |  |
|--|--|--|
| Ambient operating temperature - min  |  | -25 °C   |
| Ambient operating temperature - max  |  | 70 °C  |
| Ambient storage temperature - min  |  | 40 °C  |
| Ambient storage temperature - max  |  | 70 °C  |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>Additional information</b>  |  |  |
| Functions  |  | System and cable protection  |

## Technical data ETIM 9.0

|   |    |  |
|---|----|--|
| Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)   |    |  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecf@ss13-27-37-04-09 [AJZ716018]) |    |  |
| Rated permanent current I <sub>u</sub>  | A  | 50                                       |
| Rated voltage   | V  | 690 - 690                                |
| Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, 50 Hz   | kA | 36                                       |
| Overload release current setting  | A  | 40 - 50                                  |
| Adjustment range short-term delayed short-circuit release   | A  | 0 - 0                                    |
| Adjustment range undelayed short-circuit release  | A  | 300 - 500                                |
| Power loss  | W  | 13.2                                     |
| Device construction   |    | Built-in device fixed built-in technique |
| Integrated earth fault protection   |    | No                                       |
| Type of electrical connection of main circuit   |    | Frame clamp                              |
| Suitable for DIN rail (top hat rail) mounting   |    | No                                       |
| DIN rail (top hat rail) mounting optional   |    | Yes                                      |
| Number of auxiliary contacts as normally closed contact   |    | 0  |
| Number of auxiliary contacts as normally open contact   |    | 0  |
| Number of auxiliary contacts as change-over contact   |    | 0  |
| With switched-off indicator   |    | No                                       |
| With integrated under voltage release   |    | No                                       |
| Number of poles   |    | 3  |
| Position of connection for main current circuit   |    | Front side                               |
| Type of control element   |    | Rocker lever                             |

|                                      |  |  |      |
|--------------------------------------|--|--|------|
| Complete device with protection unit |  |  | Yes  |
| Motor drive integrated               |  |  | No   |
| Motor drive optional                 |  |  | No   |
| Degree of protection (IP)            |  |  | IP20 |