

## Miniature circuit breaker (MCB), 32 A, 4p, characteristic: K

**Part no.** FAZ-K32/4  
**279102**

**EL Number**  
**(Norway)** 1695359

General specifications		
Product name		Eaton Moeller series xEffect - FAZ MCB
Part no.		FAZ-K32/4
EAN		4015082791025
Product Length/Depth		80 millimetre
Product height		75.5 millimetre
Product width		72 millimetre
Product weight		0.474 kilogram
Compliances		RoHS conform
Certifications		IEC/EN 60947-2 IEC/EN 60898 IEC 61373 EN45545-2
Product Tradename		xEffect - FAZ
Product Type		MCB
Product Sub Type		None
Delivery program		
Application		Switchgear for industrial and advanced commercial applications xEffect - Switchgear for industrial and advanced commercial applications
Number of poles		Four-pole
Number of poles (total)		4
Number of poles (protected)		4
Tripping characteristic		K
Release characteristic		K
Amperage Rating		32 A
Type		FAZ Miniature circuit breaker
Technical Data - Electrical		
Voltage type		AC
Voltage rating		240 V AC / 415 V AC
Voltage rating at DC		60 V DC (per pole)
Rated operational voltage (Ue) - max		400 V
Rated insulation voltage (Ui)		440 V
Rated impulse withstand voltage (Uimp)		4 kV
Frequency rating - min		50 Hz
Frequency rating - max		60 Hz
Rated switching capacity (IEC/EN 60947-2)		10 kA
Operational switching capacity		7.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V		0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V		0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V		10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V		10 kA
Admissible back-up fuse - max		125 A gL/gG
Selectivity class		3
Lifespan, electrical		10000 operations
Overvoltage category		III
Pollution degree		2
Direction of incoming supply		As required
Technical Data - Mechanical		

Frame		45 mm
Enclosure width		80 mm
Width in number of modular spacings		4
Built-in depth		70.5 mm
Mounting width per pole		17.5 mm
Mounting width		17.5 mm
Mounting Method		Top-hat rail IEC/EN 60715
Mounting position		As required
Degree of protection		IP20 IP40 (when fitted)
Terminals (top and bottom)		Twin-purpose terminals
Connectable conductor cross section (solid-core) - min		1 mm <sup>2</sup>
Connectable conductor cross section (solid-core) - max		25 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - min		1 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - max		25 mm <sup>2</sup>
Terminal capacity of screw terminals for main cable		10 mm <sup>2</sup> (2x)
Terminal capacity (control cable)		25 mm <sup>2</sup> (1x)
Terminal protection		Finger and hand touch safe, DGUV VS3, EN 50274
Busbar material thickness		0.8 mm - 2 mm
<b>Design verification as per IEC/EN 61439 - technical data</b>		
Rated operational current for specified heat dissipation (In)		32 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		9.3 W
Static heat dissipation, non-current-dependent		0 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		75 °C
<b>Additional information</b>		
Current limiting class		3
Features		Concurrently switching N-neutral Additional equipment possible
Special features		Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
Used with		Miniature circuit breaker FAZ

## Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)		
Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019])		
Built-in depth	mm	70.5
Release characteristic		K
Number of poles (total)		4
Number of protected poles		4
Rated current	A	32
Rated voltage	V	400
Rated insulation voltage Ui	V	440
Rated impulse withstand voltage Uimp	kV	4
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	kA	0
Voltage type		AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	kA	0
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	10
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	10
Frequency	Hz	50 - 60
Power loss	W	9.3
Current limiting class		3
Flush-mounted installation		No

Concurrently switching neutral conductor			Yes
Over voltage category			3
Pollution degree			2
Additional equipment possible			Yes
Width in number of modular spacings			4
Degree of protection (IP)			IP20
Ambient temperature during operating		°C	-25 - 75
Connectable conductor cross section multi-wired		mm <sup>2</sup>	1 - 25
Connectable conductor cross section solid-core		mm <sup>2</sup>	1 - 25
Explosion-proof			No