

**Main switch, P5, 315 A, flush mounting, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position**

**Part no. P5-315/EA/SVB**  
**280950**

**EL Number**  
**1417187**  
**(Norway)**

<b>General specifications</b>	
Product name	Eaton Moeller® series P5 Main switch
Part no.	P5-315/EA/SVB
EAN	4015082809508
Product Length/Depth	150 millimetre
Product height	150 millimetre
Product width	130 millimetre
Product weight	1.938 kilogram
Compliances	CE Marked
Certifications	UL 508 EN 60947-3 CSA Std. C22.2 No. 14-05 IEC 60947 VDE CSA Class No.: 3211-05 IEC/EN 60204 UL CE CSA-C22.2 No. 94 CSA-C22.2 No. 14-05 UL Category Control No.: NLRV, NLRV7 VDE 0660 IEC/EN 60947 CSA File No.: 223805 CSA IEC/EN 60947-3 UL File No.: E36332 UL CSA
Product Tradename	P5
Product Type	Main switch
Product Sub Type	None
Catalog Notes	Rated Short-time Withstand Current (Icw) for a time of 1 second
<b>Features &amp; Functions</b>	
Features	Version as emergency stop installation Version as main switch Version as maintenance-/service switch
Fitted with:	Red rotary handle and yellow locking ring
Functions	Emergency switching off function Interlockable
Locking facility	Lockable in the 0 (Off) position
Number of poles	3
<b>General information</b>	
Accessories	Auxiliary contact or neutral conductor fitted by user.
Degree of protection	NEMA 12
Degree of protection (front side)	IP65
Lifespan, mechanical	80,000 Operations
Mounting method	Flush mounting
Mounting position	As required
Operating frequency	50 Operations/h
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	8000 V AC
Safe isolation	440 V AC, Between the contacts, According to EN 61140
Safety parameter (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1

Suitable for		Front mounting 4-hole Branch circuits, suitable as motor disconnect, (UL/CSA)
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		50 °C
Ambient operating temperature (enclosed) - min		-25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Terminal capacities</b>		
Terminal capacity		1 x 120 mm <sup>2</sup> , flexible with ferrules to DIN 46228 300 MCM (AWG), flexible 2 x 20 x 3 mm Number of segments x width x thickness, copper strip 1 x 185 mm <sup>2</sup> , solid or stranded 2 x 50 mm <sup>2</sup> , flexible with ferrules to DIN 46228 2 x 70 mm <sup>2</sup> , solid or stranded 1 x 20 x 5 mm Number of segments x width x thickness, copper strip 350 MCM (AWG), solid or flexible conductor with ferrule
Screw size		6 mm AF, Hexagon socket-head spanner, Terminal screw
Tightening torque		140 lb-in, Screw terminals 16 Nm, Screw terminals
<b>Electrical rating</b>		
Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)		1800 A
Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)		1650 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)		1550 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)		400 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V		147 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V		138 A
Rated operational current (Ie) at AC-3, 500 V		135 A
Rated operational current (Ie) at AC-3, 660 V, 690 V		50 A
Rated operational current (Ie) at AC-21, 440 V		315 A
Rated operational current (Ie) at AC-23A, 230 V		182 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V		205 A
Rated operational current (Ie) at AC-23A, 500 V		184 A
Rated operational current (Ie) at AC-23A, 690 V		50 A
Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms		315 A
Rated operational current (Ie) at DC-23A, 24 V		315 A
Rated operational current (Ie) at DC-23A, 48 V		315 A
Rated operational current (Ie) at DC-23A, 60 V		315 A
Rated operational current (Ie) at DC-23A, 120 V		100 A
Rated operational power at AC-3, 380/400 V, 50 Hz		75 kW
Rated operational power at AC-3, 415 V, 50 Hz		75 kW
Rated operational power at AC-3, 500 V, 50 Hz		90 kW
Rated operational power at AC-3, 690 V, 50 Hz		45 kW
Rated operational power at AC-23A, 220/230 V, 50 Hz		55 kW
Rated operational power at AC-23A, 400 V, 50 Hz		110 kW
Rated operational power at AC-23A, 500 V, 50 Hz		132 kW
Rated operational power at AC-23A, 690 V, 50 Hz		45 kW
Rated operational voltage (Ue) at AC - max		690 V
Rated uninterrupted current (Iu)		315 A
Uninterrupted current		Rated uninterrupted current Iu is specified for max. cross-section.
<b>Short-circuit rating</b>		
Rated conditional short-circuit current (Iq)		15 kA
Rated short-time withstand current (Icw)		5,8 kA, Contacts, 1 second 5.8 kA
Short-circuit current rating (basic rating)		800A Class RK1, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA)
Short-circuit current rating (high fault)		400 A, Class J, max. Fuse, SCCR (UL/CSA) 65 kA, SCCR (UL/CSA)
Short-circuit protection rating		315 A gG/gL, Fuse, Contacts

<b>Switching capacity</b>		
Load rating		2 x I# (with intermittent operation class 12, 25 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor) 1.3 x I# (with intermittent operation class 12, 60 % duty factor)
Number of contacts in series at DC-23A, 24 V		3
Number of contacts in series at DC-23A, 48 V		3
Number of contacts in series at DC-23A, 60 V		3
Number of contacts in series at DC-23A, 120 V		3
Switching capacity (main contacts, general use)		300 A, Rated uninterrupted current max. (UL/CSA)
Switching capacity (auxiliary contacts, general use)		10A, IU, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)		A600 (UL/CSA)
Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)		2050 A
Voltage per contact pair in series		42 V
<b>Motor rating</b>		
Assigned motor power at 115/120 V, 60 Hz, 1-phase		20 HP
Assigned motor power at 115/120 V, 60 Hz, 3-phase		40 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase		35 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase		75 HP
Assigned motor power at 277 V, 60 Hz, 1-phase		35 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		100 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase		100 HP
<b>Contacts</b>		
Control circuit reliability		1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
<b>Actuator</b>		
Actuator color		Red
Actuator type		Door coupling rotary drive
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		12.7 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		12.7 W
Rated operational current for specified heat dissipation (In)		315 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		UV resistance only in connection with protective shield.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss13-27-37-14-03 [AKF060018])

Version as main switch		Yes
Version as maintenance-/service switch		Yes
Version as safety switch		No
Version as emergency stop installation		Yes
Version as reversing switch		No
Number of switches		1
Max. rated operation voltage Ue AC	V	690
Rated operating voltage	V	690 - 690
Rated permanent current Iu	A	315
Rated permanent current at AC-23, 400 V	A	315
Rated permanent current at AC-21, 400 V	A	315
Rated operation power at AC-3, 400 V	kW	75
Rated short-time withstand current Icw	kA	5.8
Rated operation power at AC-23, 400 V	kW	110
Switching power at 400 V	kW	110
Conditioned rated short-circuit current Iq	kA	15
Number of poles		3
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
Motor drive optional		No
Motor drive integrated		No
Voltage release optional		No
Device construction		Built-in device fixed built-in technique
Suitable for floor mounting		No
Suitable for front mounting 4-hole		Yes
Suitable for front mounting centre		No
Suitable for distribution board installation		No
Suitable for intermediate mounting		No
Colour control element		Red
Type of control element		Door coupling rotary drive
Interlockable		Yes
Type of electrical connection of main circuit		Frame clamp
With pre-assembled cabling		No
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		12
Width	mm	130
Height	mm	150
Depth	mm	150
Width in number of modular spacings		