

RC suppressor circuit, 240 - 500 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200



**Part no. DILM95-XSPR500
281207**

| | | |
|--|--|---|
| General specifications | | |
| Product name | | Eaton Moeller® series DILM RC suppressor circuit |
| Part no. | | DILM95-XSPR500 |
| EAN | | 4015082812072 |
| Product Length/Depth | | 43 millimetre |
| Product height | | 25 millimetre |
| Product width | | 9 millimetre |
| Product weight | | 0.005 kilogram |
| Certifications | | UL Recognized UL 508 IEC/EN 60947-4-1 UL File No.: E29184 CE CSA Class No.: 3211-07 CSA-C22.2 No. 14-05 CSA UL Category Control No.: NKCR2, NKCR8 CSA File No.: 256465 |
| Product Tradename | | DILM |
| Product Type | | Accessory |
| Product Sub Type | | RC suppressor circuit |
| Catalog Notes | | With DC operated contactors and with DILM115 and DILM150 the suppressor is integrated. |
| Features & Functions | | |
| Functions | | Varistor (voltage-sensitive resistor) |
| General information | | |
| Product category | | Accessories |
| Voltage type | | AC |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 60 °C |
| Magnet system | | |
| Rated control supply voltage (Us) at AC, 50 Hz - min | | 240 V |
| Rated control supply voltage (Us) at AC, 50 Hz - max | | 500 V |
| Rated control supply voltage (Us) at AC, 60 Hz - min | | 240 V |
| Rated control supply voltage (Us) at AC, 60 Hz - max | | 500 V |
| Rated control supply voltage (Us) at DC - min | | 0 V |
| Rated control supply voltage (Us) at DC - max | | 0 V |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |

| | | | |
|--|--|--|--|
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|--|--|---|---------------------------------------|
| Low-voltage industrial components (EG000017) / Surge protection module (EC000683) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Component for protective circuit (ecl@ss13-27-37-10-10 [AKF019018]) | | | |
| Function | | | Varistor (voltage-sensitive resistor) |
| Voltage type (operating voltage) | | | AC |
| Operating voltage AC 50 Hz | | V | 230 - 690 |
| Operating voltage AC 60 Hz | | V | 230 - 690 |
| Operating voltage DC | | V | 0 - 0 |
| With LED indication | | | No |