



Oil fuse-link, medium voltage, 40 A, AC 3.6 kV, 50 kA, BS2692 F01, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight

Part no. 3.6KV 40AMP 2.5" OIL FUSE
Catalog No. 3.60EFMA40

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Oil fuse-link
Field of application			medium voltage
Rated current	I	A	40
Rated voltage			AC 3.6 kV
Construction size			BS2692 F01
Size			254 x 63.5 mm
Utilization category			back-up
Status indicator			with striker
Description			oil-tight
Breaking Capacity		kA	50
usable for size/applications			protection of primary side transformer, and oil-filled fuse switch combination unit
Standard/Approval			BS IEC ESI
Shape			cylindrical
Standards/Regulations			BS2692-1 IEC 60282-1 ESI 12-8

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	40
Rated voltage		kV	3.6
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	50
Utilization category			Other
Application			Primary side transformer protection
Length		mm	254
Diameter		mm	63.5
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Oil

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf
-------------------------	---