



Fuse-link, low voltage, 50 A, AC 400 V, 50 kA, D02, gL/gG, IEC, time-delay



**Part no.** FUSE-D02 50A T GL/GG 400VAC E18  
**Catalog No.** 50NZ02

**EL-Nummer (Norway)** 1600284

Similar to illustration

### Delivery program

|                              |       |    |   |
|------------------------------|-------|----|---|
| Product range                |       |    | Fuse  |
| Basic function               |       |    | Fuse-link   |
| Field of application         |       |    | low voltage   |
| Rated current                | I     | A  | 50  |
| Rated voltage                |       |    | AC 400 V  |
| Construction size            |       |    | D02   |
| Utilization category         |       |    | gL/gG   |
| Breaking Capacity            |       | kA | 50  |
| usable for size/applications |       |    | E18<br>for domestic and general industrial applications |
| Release characteristic       | class |    | time-delay  |
| Standard/Approval            |       |    | IEC   |
| Shape                        |       |    | bottle  |
| Standards/Regulations        |       |    | IEC 60269-3<br>VDE 0636                                 |

### Technical data ETIM 7.0

|   |  |   |   |
|---|--|---|---|
| Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)  |  |   |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011]) |  |   |   |
| Construction size   |  |   | D02   |
| Rated current   |  | A | 50  |
| Rated voltage   |  | V | 400   |
| Colour code   |  |   | White   |
| Utilization category  |  |   | gL/gG (cable protection/equipment protection) |