



Eaton 5E 1500i USB

Part no.
Catalog No.

Eaton 5E 1500i USB
5E1500IUSB

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecI@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	170 - 280
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	230 - 230
Secondary frequency	Hz	50 - 60
Output effective power	W	900
Output apparent power	VA	1500
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	180
Width	mm	133
Depth	mm	330
Transition time for full load	min	1
Weight	kg	10.46
Network-management		No
USV- technology		Line-interactive
Construction type		Free standing model
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	95
Efficiency in eco-mode	%	95
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		C14
Number of output connections C13		6
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0