



Eaton 5PX 3000i RT2U Netpack

Part no.

Catalog No.

Eaton 5PX 3000i RT2U Netpack

5PX3000IRTN



Powering Business Worldwide™

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec@ss10.0.1-27-04-06-90 [BAB258012])		
Input voltage	V	160 - 294
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	200 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	2700
Output apparent power	VA	3000
Type of interface		Other
Number of phases secondary		1
SNMP		Yes
Voltage type		AC
Height	mm	86.2
Width	mm	441.2
Depth	mm	647
Transition time for full load	min	3
Weight	kg	38.08
Network-management		Yes
USV- technology		Line-interactive
Construction type		482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%	0
Output power factor		0.9
Overall efficiency	%	94
Efficiency in eco-mode	%	94
Potential free switch contact		Yes
Auto shut down function		Yes
Input connection		C20
Number of output connections C13		8
Number of output connections C19		1
Number of output connections with protective contact (SCHUKO)		0
Number of output connections fixed connection		0