



VT fuse-link, medium voltage, 3.15 A, AC 7.2 kV, 142 x 25.4 mm, back-up, BS, IEC, style 22 tags

Part no. 7.2KV 3.15A VT FUSE
Catalog No. 7.20BWN223.15

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|------------------------------------|
| Product range | | | Fuse |
| Basic function | | | VT fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 3.15 |
| Rated voltage | | | AC 7.2 kV |
| Size | | | 142 x 25.4 mm |
| Utilization category | | | back-up |
| Breaking Capacity | | kA | 45 |
| usable for size/applications | | | voltage and auxiliary transformers |
| Standard/Approval | | | BS IEC |
| Shape | | | cylindrical |
| Standards/Regulations | | | BS2692-1 IEC 60282-1 |

Technical data ETIM 7.0

| | | | |
|--|--|----|----------------------------------|
| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) | | | |
| Rated current | | A | 3.15 |
| Rated voltage | | kV | 7.2 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 50 - 50 |
| Breaking capacity | | kA | 45 |
| Utilization category | | | Other |
| Application | | | Auxiliary transformer protection |
| Length | | mm | 142 |
| Diameter | | mm | 25.4 |
| Performance category according to IEC 60282-1 | | | Back-up |
| With striker | | | No |
| Standard | | | British Standard |
| Release characteristic | | | Other |
| Installation technique | | | Oil |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf |
|-------------------------|---|