

**Variable frequency drive, 230 V AC, 3-phase, 25 A, 5.5 kW, IP54/NEMA12,
Brake chopper, DC link choke**



Part no. DG1-32025FB-C54C

9701-2105-00P

**EL Number
(Norway)**

4138050

General specifications		
Product name		Eaton DG1 variable frequency drive
Part no.		DG1-32025FB-C54C
EAN		4015081734214
Product Length/Depth		244.7 millimetre
Product height		419 millimetre
Product width		167.8 millimetre
Product weight		10.2 kilogram
Certifications		UL508 UkrSEPRO UL report applies to both US and Canada IEC/EN61800-5 Certified by UL for use in Canada Specification for general requirements: IEC/EN 61800-2 EAC IEC/EN 61800-3 UL Category Control No.: NMMS, NMMS7 CSA-C22.2 No. 274-13 UL Safety requirements: IEC/EN 61800-5 RoHS, ISO 9001 UL File No.: E134360 IEC/EN61800-3 CE CUL C-Tick
Product Tradename		DG1
Product Type		Variable frequency drive
Product Sub Type		None

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency / Servo converter = < 1 kV (ecl@ss13-27-02-31-01 [AKE177019])		
Mains voltage	V	208 - 240
Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3
Max. output frequency	Hz	400
Max. output voltage	V	240
Nominal output current I2N	A	25
Max. output at quadratic load at rated output voltage	kW	7.5
Max. output at linear load at rated output voltage	kW	5.5
Power consumption	W	315
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		2
Number of analogue inputs		2
Number of digital outputs		1
Number of digital inputs		8
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes

Supporting protocol for CAN			Yes
Supporting protocol for INTERBUS			No
Supporting protocol for ASI			No
Supporting protocol for KNX			No
Supporting protocol for Modbus			Yes
Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			Yes
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			Yes
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			Yes
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for BACnet			Yes
Supporting protocol for other bus systems			Yes
Number of HW-interfaces industrial Ethernet			1
Number of interfaces PROFINET			0
Number of HW-interfaces RS-232			0
Number of HW-interfaces RS-422			0
Number of HW-interfaces RS-485			1
Number of HW-interfaces serial TTY			0
Number of HW-interfaces USB			0
Number of HW-interfaces parallel			0
Number of HW-interfaces other			1
With optical interface			No
With PC connection			Yes
Integrated breaking resistance			Yes
4-quadrant operation possible			Yes
Type of converter			U converter
Degree of protection (IP)			IP54
Degree of protection (NEMA)			12
Height		mm	419
Width		mm	167.8
Depth		mm	244.7