DATASHEET - 10733971



Fuse-link, LV, 12 A, AC 690 V, 14 x 51 mm, gL/gG, IEC



EL Number (Norway) C14G12 1600236

Similar to illustration

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	C14G12
EAN	5027590493826
Product Length/Depth	51 millimetre
Product height	14.3 millimetre
Product width	14.3 millimetre
Product weight	20.3 gram
Compliances	RoHS Compliant GoST-R CE Marked
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	12 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	80 kA
Utilization category	gL/gG (cable protection/equipment protection)
Suitable for	CH14 Modular fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])			
Model		Ceramic fuse	
Size		14x51 mm	
Voltage type		AC	
Rated current	Α	12	
Rated voltage	V	690	
Utilization category		gL/gG (cable protection/equipment protection)	
Rated operating frequency	Hz	45 - 62	
Type of fuse status indicator		Other	
Release characteristic		Other	
Breaking capacity	kA	80	
Power loss at rated current	W	1.7	