



Fuse-link, LV, 16 A, AC 500 V, 14 x 51 mm, gL/gG, IEC, with striker

C14G16S

Similar to illustration

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	CYL FUSE >STR >14 x 51 16A GG 690V AC
EAN	5027590493888
Product Length/Depth	51 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	20.7 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	16 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Utilization category	gG (cable protection/equipment protection)
Suitable for	CH14 Modular fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC
Rated current	A	16
Rated voltage	V	500
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Top fuse status indicator
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	2