

DATASHEET - 1A 240V PLUG TOP FUSE



Fuse-link, Overcurrent NON SMD, 1 A, AC 240 V, 6 kA, BS1362 plug fuse, 6.3 x 25 mm, gL/gG, BS



Part no. 1A 240V PLUG TOP FUSE
Catalog No. C180-1A

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			Overcurrent NON SMD
Rated current	I	A	1
Rated voltage			AC 240 V
Construction size			BS1362 plug fuse
Size			6.3 x 25 mm
Utilization category			gL/gG
Breaking Capacity		kA	6
usable for size/applications			use in BS1363 plugs
Standard/Approval			BS
Shape			cylindrical
Standards/Regulations			BS1362 IEC 60269-3

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Miniature fuse (EC000035)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])			
Connection type			Other
Voltage type			AC
Release characteristic			Fast (F)
Model			Ceramic fuse
Rated current		A	1
Rated voltage		V	240
Dimensions			Other
Optical defect indication			No