



Fuse-link, Overcurrent NON SMD, 5 A, AC 240 V, 6 kA, BS1362 plug fuse, 6.3 x 25 mm, gL/gG, BS

Part no. 5A 240V PLUG TOP FUSE
Catalog No. C180-5A

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|-----------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | Overcurrent NON SMD |
| Rated current | I | A | 5 |
| Rated voltage | | | AC 240 V |
| Construction size | | | BS1362 plug fuse |
| Size | | | 6.3 x 25 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 6 |
| usable for size/applications | | | use in BS1363 plugs |
| Standard/Approval | | | BS |
| Shape | | | cylindrical |
| Standards/Regulations | | | BS1362 IEC 60269-3 |

Technical data ETIM 7.0

| | | | |
|---|--|---|--------------|
| Circuit breakers and fuses (EG000020) / Miniature fuse (EC000035) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | | |
| Connection type | | | Other |
| Voltage type | | | AC |
| Release characteristic | | | Fast (F) |
| Model | | | Ceramic fuse |
| Rated current | | A | 5 |
| Rated voltage | | V | 240 |
| Dimensions | | | Other |
| Optical defect indication | | | No |