



Fuse-holder, low voltage, 50 A, AC 690 V, 14 x 51 mm, 1P, IEC, With indicator

**CH141DIU**

Product name	Eaton Bussmann series low voltage cylindrical fuse holder
Part no.	1P 14x51 Neon Indicator Fuse Holder
EAN	5027590496612
Product Length/Depth	76 millimetre
Product height	92 millimetre
Product width	27 millimetre
Product weight	87.333 gram
Compliances	CE Marked RoHS Compliant
Certifications	EAC IEC 60269-2 UL Listed File E14853 IEC 60269-1
Product Tradename	None
Product Type	Low voltage cylindrical fuse holder
Product Sub Type	None
Amperage Rating	50 A
Voltage rating at AC	690 V a.c. (IEC) and 700 V a.c. (UL)
Voltage rating at DC	750 V d.c. (IEC)
Mounting method	DIN rail 2 x M4 Panel mounting screws
Optical defect indication	Yes
Fitted with:	Neon indicator
Degree of protection	IP20
Built-in depth	51.5 mm
Lockable	Yes
Width in number of modular spacings	1.5
Application	Industrial and Commercial applications
Fuse size	14 x 51 mm
Fuse type	C14G C14M
Accessories	JV-L Multipole connector kit, CH14-CTP IP20 Protection accessory, CH14-SPS Microswitch to work with CH141D(I)U, CH14-SPS Microswitch to work with CH141D(I)U

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss10.0.1-27-14-21-21 [ADI305007])		
Nominal voltage	V	690
Mounting method		DIN rail
For fuse size		14x51 mm
Number of poles		1
Concurrently switching neutral conductor		No
Lockable		Yes
With optical defect indication		Yes
Width in number of modular spacings		1.5

Built-in depth	mm	51.5
Degree of protection (IP)		IP20