



Fuse-link, high speed, 100 A, AC 600 V, DC 450 V, 200 kA, 29 x 118 mm, J, UL, CSA

Part no.
Catalog No.

DRIVE FUSE
DFJ-100

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	100
Rated voltage			AC 600 V DC 450 V
Size			29 x 118 mm
Utilization category			J
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			UL CSA
Shape			cylindrical with centre-bolted tags
Standards/Regulations			UL 248-8

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	100
Rated voltage		V	600
Voltage type			AC/DC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1048_DFJ.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/high_speed_/dfj.html