

EBH103TS8

| | | |
|----------------------|--|---|
| Product name | | Eaton Busmann series low voltage NH fuse base |
| Part no. | | EBH103TS8 |
| EAN | | 5906739010707 |
| Product Length/Depth | | 270 millimetre |
| Product height | | 130 millimetre |
| Product width | | 185 millimetre |
| Product weight | | 2349 gram |
| Compliances | | CE |
| Product Tradename | | None |
| Product Type | | Low voltage NH fuse base |
| Product Sub Type | | None |
| Amperage Rating | | 250 A |
| Voltage rating | | 690 |
| Number of poles | | Three-pole |
| Mounting method | | 60 mm busbar mounting 100 mm busbar mounting Mounting plate |

Technical data ETIM 8.0

| | | |
|--|----|-------------|
| Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013]) | | |
| Version as main switch | | No |
| Version as safety switch | | No |
| Max. rated operation voltage Ue AC | V | 690 |
| Rated permanent current Iu | A | 250 |
| Rated operation power at AC-23, 400 V | kW | 0.1 |
| Conditioned rated short-circuit current Iq | kA | 0.08 |
| Rated short-time withstand current Icw | kA | 80 |
| Suitable for fuses | | NH1 |
| Number of poles | | 3 |
| With error protection | | No |
| Type of electrical connection of main circuit | | Cable clamp |
| Cable entry | | Other |
| Equipped with connectors | | No |
| Suitable for floor mounting | | No |
| Suitable for front mounting | | Yes |
| Suitable for busbar mounting | | No |
| Type of control element | | Cover grip |
| Position control element | | Front side |
| Motor drive optional | | No |
| Motor drive integrated | | No |
| Version as emergency stop installation | | No |
| Degree of protection (IP), front side | | IP30 |