



Eaton FlexPDU, 1U, C20 input, 4 kW, 16A, 200-240V, Outlets: (1) C19/(8) PC/
SHUKO, DIN



Catalog No. EFLX8D

Similar to illustration

Delivery program

Fitted With:		Mounting material
Type		Rack PDU
Input Connection		C20
Cord Length		2m
Input Voltage		200-240V
Phase		Single-phase
Frequency Rating		50/60 Hz
Ethernet Interface		No
Serial Interface		No
Form Factor		1U
Outlet Control		No
Operating Temperature		0° to 60°C (32° to 140°F)
Number of Outputs C13		0
Number of Outputs C19		1
Amperage Rating		16A
Mounting Direction		Horizontal
ETIM Class		EC002762
Electrical Connection		Socket outlet
Evaluation		Other
Mounting Dimension (metrical)		44
Mounting Dimension (standardised)		482.6 mm (19 inch)
Switchable		No
Over Voltage Category		2
Wattage		3.84 kW max
SNMP		No
Mass Configuration		No
Package Contents		PDU mounting accessories Quickstart Safety Instructions
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		8
Number of Outputs (Other)		8
Number of Outlets with Earth Pin		0
Color		Black

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	
Mounting direction		Horizontal
Electrical connection		Socket outlet
Type of electric connection		C20
Cable length	m	2
Number of socket outlets with protective contact		8
Number of socket outlets with earth pin		0
Number of C13 socket outlets		0
Number of C19 socket outlets		1
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		
Number of height units		
Length	mm	80
Width	mm	483
Height	mm	44
Depth	mm	80
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		No
With display		No
Evaluation		Other
With LED indication		No
With fuse		No
Ampere meter		No
With temperature measurement		No
With mounting material		Yes