

Circuit-breaker, 3p, 2000A, fixed



Part no. IZM32B3-P20F-1
EP-500163

Product name	Eaton IZM32/IN32 circuit-breaker
Part no.	IZM32B3-P20F-1
EAN	9010653016076
Product Length/Depth	511 millimetre
Product height	514 millimetre
Product width	492 millimetre
Product weight	60.325 kilogram
Compliances	IEC IEC/EN 60947
Product Tradename	IZM32/IN32
Product Type	Circuit-breaker
Product Sub Type	None
Globally Marketable	Yes
Actuator color	Green
Actuator type	Push button
Adjustment range short-term delayed short-circuit release - max	20000 A
Adjustment range short-term delayed short-circuit release - min	1200 A
Adjustment range short-term delayed short-circuit release [7EF007129]	A
Adjustment range undelayed short-circuit release - max	30000 A
Adjustment range undelayed short-circuit release - min	4000 A
Adjustment range undelayed short-circuit release [7EF007131]	A
Ambient operating temperature - max	70 °C
Ambient operating temperature - min	-20 °C
Ambient storage temperature - max	70 °C
Ambient storage temperature - min	-20 °C
Amperage Rating	2000 A
Breaking time	40 ms
Closing delay via spring release	30 ms
Degree of protection	IP20 IP41 with door sealing frame IP55 with protective cover
Device construction	Built-in device fixed built-in technique
Direction of incoming supply	As required
Electrical connection type of main circuit	Rail connection
Features	Complete device with protection unit Motor drive optional
Fitted with:	Switched-off indicator
Frame	IZM32
Heat dissipation at rated current with fixed mounting	190 W
Mounting Method	Fixed
Number of auxiliary contacts (change-over contacts)	4
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0
Number of poles	Three-pole
Number of standard mechanical operations per hour - max	60
Operating sequence up to 690 V, 50/60 Hz (IEC/EN 60947)	65 kA
Overload release current setting - max	2000 A
Overload release current setting - min	800 A
Overload release current setting [7EF002336]	A

Overvoltage category		III
Pollution degree		3
Position of connection for main current circuit		Back side
Power of withdrawable switch with cassette		330 W
Protection		Universal protection and power measurement
Rated impulse withstand voltage (Uimp)		8 kV AC
Rated insulation voltage (Ui)		1000 V
Rated operating voltage (Ue) - min		690 V
Rated operating voltage (Ue) at AC - max		690 V
Rated permanent current Iu [7EF001389]		A
Rated short-circuit breaking capacity (IEC/EN 60947) up to 240 V, 50/60Hz		kA
Rated short-circuit breaking capacity (IEC/EN 60947) up to 440 V, 50/60Hz		kA
Rated short-circuit breaking capacity (IEC/EN 60947) up to 690 V, 50/60Hz		kA
Rated short-circuit breaking capacity at 400 V, 50 Hz		66 kA
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz [7EF007048]		kA
Rated short-circuit making capacity up to 440 V, 50/60 Hz		145 kA
Rated short-circuit making capacity up to 690 V, 50/60 Hz		137 kA
Rated short-time withstand current (t = 1 s)		65 kA
Rated short-time withstand current at 50/60 Hz (t = 3 s)		50 kA
Rated uninterrupted current (Iu)		2000 A
Rated uninterrupted current (Iu) at 50°C		2000 A
Rated uninterrupted current (Iu) at 60°C		2000 A
Rated uninterrupted current (Iu) at 70°C		2000 A
Rated voltage [7EF003977]		V
Release system		Electronic release
Suitable for		Main conducting paths with 65 kA in IT electrical power networks up to U = 440 V
Terminal capacity (copper bar)		5 mm x 100 mm (3x) for fixed mounting (black) 5 mm x 100 mm (3x) for withdrawable units (black)
Type		Air circuit breakers/switch-disconnector Open circuit breaker
Utilization category		B
Voltage rating at AC		690 V AC
Weight of cassette version (3-pole)		58 kg
Weight of cassette version (4-pole)		60 kg
Weight of fixed mounting version (3-pole)		63 kg
Weight of fixed mounting version (4-pole)		78 kg
Weight of fixed withdrawable version (3-pole)		75 kg
Weight of fixed withdrawable version (4-pole)		94 kg