

EVGK busbar fork, 3-phase, L1 - L2 - L3, shortenable version with end caps included, 12 module units, 10 mm²



**Part no. EVGK-3PHAS/12MODUL
EP-501069**

Product name		Eaton Moeller series busbar
Part no.		EVGK-3PHAS/12MODUL
EAN		9010653035138
Product Length/Depth		213 millimetre
Product height		28.5 millimetre
Product width		15 millimetre
Product weight		0.081 kilogram
Certifications		CE
Product Tradename		None
Product Type		Busbar
Product Sub Type		None
Countries		Mexico
Color		Grey
Cross section		10 mm ²
Electric connection type		Fork
Features		Insulated
Nominal current		63 A
Number of modular spacings		12
Number of phases		3
Number of poles		Three-pole
Pitch dimensions		17.8 mm
Rated conditional short-circuit current (I _q)		25 kA
Rated operating voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		4 kV
Rated uninterrupted current (I _u)		63 A
Suitable for		4 devices

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011])		
Number of phases		3
Number of poles		3
Suitable for number of devices		4
Module width	mm	17.8
Cross section	mm ²	10
Length	mm	213
Width in number of modular spacings		12
Rated permanent current I _u	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I _q	kA	25
Max. rated operation voltage U _e	V	415
Rated short-time withstand current I _{cw}	kA	0

Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Grey