



**Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 16A 1Ph, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19**



**Catalog No.            ESWB04**

**Delivery program**

Type			Rack PDU
Input Connection			IEC-60309 16A 1Ph
Cord Length			3m
Input Voltage			200-240V
Phase			Single-phase
Frequency Rating			50/60 Hz
Ethernet Interface			Yes
Serial Interface			Yes
Form Factor			0U (Vertical)
Outlet Control			Yes
Operating Temperature			0° to 60°C (32° to 140°F)
Outlets			20XC13 : 4XC19
Number of Outputs C13			20
Number of Outputs C19			4
Amperage Rating			16A
Mounting Direction			Vertical
ETIM Class			EC002762
Fitted With:			Display Mounting material Ampere Meter
Electrical Connection			Connecting cord with plug
Evaluation			At distance
Mounting Dimension (metrical)			52
Mounting Dimension (standardised)			Metric
Switchable			Yes
Over Voltage Category			2
Wattage			3.84 kW max
Communication			HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP			Yes
Mass Configuration			Yes
Package Contents			PDU, Mounting accessories, Network cable, Configuration cable, Splitter for daisy-chaining, Quickstart guide, Safety Instructions
Number of Outputs C20			0
Num of Outputs PC (SCHUKO)			0
Number of Outputs (Other)			0
Number of Outlets with Earth Pin			24
Color			Black

**Technical data ETIM 7.0**

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)			
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])			
Mounting dimension (standardised)			Metric
Mounting dimension		mm	
Mounting direction			Vertical
Electrical connection			Connecting cord with plug
Type of electric connection			Other
Cable length		m	3
Number of socket outlets with protective contact			0
Number of socket outlets with earth pin			24
Number of C13 socket outlets			20
Number of C19 socket outlets			4
Number of C20 socket outlets			0
Number of UK BS1363 sockets			
number of socket outlets swiss standard type 13			
number of socket outlets swiss standard type 15			
number of socket outlets swiss standard type 23			
number of socket outlets swiss standard type 25			
Number of other socket outlets			
Number of height units			
Length		mm	1,604
Width		mm	53
Height		mm	52
Depth		mm	1,604
Supply voltage		V	
Over voltage category			2
Mains filter			No
Switchable			Yes
SNMP			Yes
With display			Yes
Evaluation			At distance
With LED indication			No
With fuse			No
Ampere meter			Yes
With temperature measurement			No
With mounting material			Yes