



Fuse-link, high speed, 2500 A, AC 250 V, 48 x 89 mm, UL

FWX-2500AH

Similar to illustration

Product name	Eaton Bussmann series high speed cylindrical fuse
Part no.	FWX-2500AH
EAN	5027590022026
Product Length/Depth	65 millimetre
Product height	90 millimetre
Product width	90 millimetre
Product weight	1951 gram
Compliances	CE Marked RoHS Compliant
Certifications	CSA Certified UL Recognized
Product Tradename	None
Product Type	High speed cylindrical fuse
Product Sub Type	None
Amperage Rating	20 A
Voltage rating	250 Vac, 250 Vdc
Voltage type	AC/DC
Interrupt rating	200 kAIC Vac 50 kAIC at 250 Vdc
Class	Class aR
Clearing (I ₂ T)	4700000 at 250 V
Application	Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator	Non Indicating

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC
Rated voltage AC	V	250
Rated voltage DC	V	
Rated current	A	20
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	163
Mounting holes		Other
Centre-to-centre distance of connections	mm	65.8