

NSD32M40

General specifications		
Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		NSD32M40
EAN		5027590504904
Product Length/Depth		59 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		26 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269-2 BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		40 A
Voltage rating		415 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gM
Product specifications		
Application		general industrial applications
Fuse type		NSD
Fuse size		BS88/F1
Fitted with:		Offset bladed tags
Connection		Blade end
Compatible fuse holder		
Suitable for		32NNS Safeloc fuse holder SC32 Safeclip fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Fuse system E
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	40
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.9
Mounting holes		
Centre-to-centre distance of connections	mm	