

Spécifications

Eaton PDUMV20HV



Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, C20/L6-20P input, 10 ft cord, 3.7kW, 16A, 208/230V, 38 Outlets (32) C13 (6) C19



Spécifications générales

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Tripp Lite series local metered rack PDU |
| CATALOG NUMBER | PDUMV20HV |
| UPC | 037332139344 |
| PRODUCT LENGTH/DEPTH | 63.75 in |
| PRODUCT HEIGHT | 3.75 in |
| PRODUCT WIDTH | 2.25 in |
| PRODUCT WEIGHT | 5.2 lb |
| COMPLIANCES | EAC CE Marked RoHS TAA Compliant |
| CERTIFICATIONS | NOM GoST-R RETIE IEC 62368-1 |



Powering Business Worldwide

Spécifications du produit

Ressources

| | |
|---------------------------------------|---|
| FORM FACTOR | 0U (Vertical) |
| PACKAGE CONTENTS | <ul style="list-style-type: none">• PDUMV20HV 63.75 inch basic PDU• Plug-lock inserts (6 C20, 32 C13)• Spare installation buttons, 2.9 mm/4.6 mm• 10-ft. (3.05 m) detachable C19-to-L620P input cordset• Mounting hardware• Owner's Manual |
| OPERATING TEMPERATURE | 32° to 104°F (0° to 40°C) |
| MOUNTING DIRECTION | Vertical |
| MATERIAL | Aluminum |
| INPUT CONNECTION | L6-20P |
| CORD LENGTH | 10 ft |
| AMPERAGE RATING | 16A |
| ELECTRIC CURRENT - MAX | 16 |
| PHASE | Single-phase |
| FREQUENCY RATING | 50/60 Hz |
| NUMBER OF OUTPUTS C13 | 32 |
| NUMBER OF OUTPUTS C19 | 6 |
| FEATURES | Flex Center |
| FRONT PANEL LCD DISPLAY | Digital meter reports PDU output current in amps |
| OUTPUT RECEPTACLES | C13 C19 |
| RECOMMENDED ELECTRICAL SERVICE | Single-phase 16/20A 230/208V service |
| OUTPUT RECEPTACLES DETAILS | Compatible with Eaton Tripp Lite Power Cords |
| RECEPTACLES | <ul style="list-style-type: none">• C13• C19 |
| INPUT CORD LENGTH | 10 ft |
| TAA COMPLIANCE | No |
| PRODUCT FEATURES | L6-20P detachable cordset, C20 inlet available |
| AMPERAGE RATING | Agency de-rated to 16A |

| | |
|------------------------------------|---|
| DETAILS | continuous |
| OPERATING ELEVATION | 0-10000 ft. (0-3000 m) |
| OPERATING TEMPERATURE RANGE | 32° to 104°F (0° to 40°C) |
| OUTPUT NOMINAL VOLTAGE | 208/230V |
| RELATIVE HUMIDITY | 0-95% non-condensing |
| FORM FACTORS SUPPORTED | 0u vertical installation in equipment racks, plus under-counter and wallmount |
| OUTPUT CAPACITY DETAILS | 3.68kW (230V), 3.33kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet |
| OUTPUT CAPACITY (KW) | 3.7 |
| STORAGE TEMPERATURE | -22° to 122°F (-30° to 50°C) |
| PRODUCT HIGHLIGHTS | <p>Ready for immediate toolless 0U installation</p> <p>C20 inlet accepts a variety of 16A international cordsets</p> <p>10ft / 3m detachable input cable with NEMA L6-20P plug</p> <p>38 output receptacles (6 C19, 32 C13); Compatible with Eaton Tripp Lite power cords</p> <p>Local metered single phase 16A 208/230V 0U</p> <p>63.75in / 162cm vertical rackmount PDU</p> <p>Two-digit meter reports output current in amps</p> |
| PDU PLUG TYPE | L6-20P |
| PDU TYPE | Local metered |
| PDU INPUT VOLTAGE | 208 |
| PDU FORM FACTOR | Vertical (0U) |
| TOTAL OUTLETS | 38 |

NOM DU PROJET:

NUMÉRO DU PROJET:

PRÉPARÉ PAR:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlande
Eaton.com

© 2026 Eaton. Tous droits réservés.

Suivez-nous sur les réseaux sociaux
pour connaître les dernières
informations concernant nos
produits.

