

DATASHEET - RED SPOT 20 AMP FRONT CONNECTED



Fuse holder, low voltage, 20 A, AC 690 V, BS88/A1, 1P, BS, front connected,
Paint finish



Powering Business Worldwide™

Part no. **RED SPOT 20 AMP FRONT CONNECTED**
Catalog No. **RS20H**

Delivery program

| | | | |
|------------------------------|---|---|---------------------------------|
| Product range | | | Fuse accessory |
| Basic function | | | Fuse-holder |
| Field of application | | | low voltage |
| Rated current | I | A | 20 |
| Rated voltage | | | AC 690 V |
| Construction size | | | BS88/A1 |
| Description | | | front connected Paint finish |
| Protection | | | IP20 |
| Number of poles | | | 1P |
| usable for size/applications | | | NITD and NIT fuse-links |
| Standard/Approval | | | BS |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |

Technical data ETIM 7.0

| | | | |
|--|--|---|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss10.0.1-27-14-21-06 [AKE278013]) | | | |
| Construction size | | | Other |
| Number of poles | | | 1 |
| Rated current | | A | 20 |
| Bus-mounting type | | | No |
| Swivelling mechanism | | | No |