



Fuse-link, LV, 63 A, AC 660 V, DC 460 V, BS88/A3, 22 x 86 mm, gL/gG, BS

**TIS63**

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		TIS63
EAN		5027590514347
Product Length/Depth		84.5 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		49.5 gram
Compliances		Contact Manufacturer
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		63 A
Voltage rating		690 V
Voltage type		AC/DC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		TIS
Fuse size		BS88/A3
Fitted with:		Offset bolted tags
Connection		73 mm fixing centre
Suitable for		CM63F Camaster fuse holder RS63 Red spot fuse holder

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A3
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	460
Rated current	A	63
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M5
Centre-to-centre distance of connections	mm	73