

Cable grommet, PG16, IP65

Part no. **KT16**
 022031
 EL Number **4132342**
 (Norway)

General specifications		
Product name		Eaton xEffect Accessories cable grommet PG
Part no.		KT16
EAN		4015080220312
Product Length/Depth		15 millimetre
Product height		25 millimetre
Product width		25 millimetre
Product weight		0.004 kilogram
Compliances		RoHS conform
Product Tradename		xEffect Accessories
Product Type		Cable grommet
Product Sub Type		PG
Delivery program		
Type		General switchboard accessory
Model		Closed
Accessory/spare part type		Cable management Cable grommets
Color		Gray
Technical Data - Mechanical		
Bore diameter		23.5 mm
Surface finishing		Similar RAL 7035
Surface protection		Other
Material		Cadmium- and lead-free Soft PVC Plastic
Material quality		Polyvinyl chloride (PVC)
Degree of protection		IP65
Number of cables - min		1
Number of cables - max		1
Operating temperature - min		-5 °C
Operating temperature - max		40 °C
For outer cable diameter - min		7 mm
For outer cable diameter - max		17 mm
For wall thickness - min		2 mm
For wall thickness - max		8 mm
Cable entry type		PG 16 Round
Opening diameter		23.5 mm
Thread size		0
Suitable for cable diameter - min		7 mm
Suitable for cable diameter - max		17 mm
Additional information		
Features		Gastight Watertight
Used with		NYM/NYY 4 core, 1.5 mm ² - 10 mm ² For wall thickness 2 - 8 mm

Technical data ETIM 9.0

Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879)

Electric engineering, automation, process control engineering / Electrical installation, device / Cable gland / Additional components cable gland (ec|@ss13-27-14-08-07 [AHD200002])

Model		Closed
Suitable for cable gland		No
Cable entry		Round
Number of cables		1 - 1
Suitable for cable diameter	mm	7 - 17
Bore diameter	mm	23.5
For wall thickness	mm	2 - 8
Thread size (metric)		0
Thread size PG		16
Total length	mm	15
With strain relief		No
Shrink technique		No
Angle model		No
Material		Plastic
Material quality		Polyvinyl chloride (PVC)
Surface protection		Other
Halogen free		No
Colour		Grey
Gastight		Yes
Fire resistant		No
Watertight		Yes
Degree of protection (IP)		IP65
Operating temperature	°C	-5 - 40