


Connection terminal, 400A, 3p, flat/round









Part no. **K240/3**
Catalog No. **039255**

EL-Nummer **4132418**
(Norway)

Delivery program

Product range			General switchboard accessories
Product function			Accessories panel building
Accessories			Terminations
Accessories			Terminals, 160 – 1000 A
Rated insulation voltage	U _i	V AC	1000
Description			Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN,  Relationship of rated operational current → terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021 Outer terminal for round or sectoral conductor, other side for Cu strip
Rated operational current	I _e	A	400
Pole			3

Terminal capacity

Cu/Al cable			<ul style="list-style-type: none"> Cu  Round stranded  Sectoral stranded  Round solid  Sectoral solid Al  Round solid  Sectoral solid
			<ul style="list-style-type: none"> 1 x 50 - 240 2 x 25 - 120
Al cable			<ul style="list-style-type: none"> Al  Sectoral solid
			<ul style="list-style-type: none"> 1 x 95 - 185 2 x 50 - 95
Copper band		mm	<ul style="list-style-type: none"> 6 x 16 x 0.8 10 x 16 x 0.8
			# copper strip
conductor			<ul style="list-style-type: none"> 25 x 15  Cu bar

Notes Conversion kits for strip terminal in cable connection available separately
Terminal covers available separately

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Rail terminal bar (EC000275)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ec@ss10.0.1-27-40-06-03 [ACO369011])			
Number of poles			3
Nominal current		A	400
Connection type			Screwing
Mounting method			Screw
Number of connections total			6
Number of connections < 6 mm ²			0
Number of connections 10 mm ²			0
Number of connections 16 mm ²			0
Number of connections 25 mm ²			0

Number of connections > 25 mm ²			6
Number of connections < AWG 6			0
Number of connections AWG 6			0
Number of connections AWG 4			0
Number of connections AWG 2			0
Number of connections AWG 4/0			0
Number of connections 250 kcmil			0
Number of connections > 250 kcmil			0
Contact safe			Yes
Height		mm	100
Width		mm	144
Depth		mm	115