

Top-hat rail 35x7.5mm



**Part no.** TS35X7,5  
**053030**  
**EL Number** 1654945  
**(Norway)**

General specifications		
Product name		Eaton xEffect Accessories mounting part
Part no.		TS35X7,5
EAN		4015080530305
Product Length/Depth		2000 millimetre
Product height		8 millimetre
Product width		35 millimetre
Product weight		0.634 kilogram
Compliances		RoHS conform
Certifications		according to IEC/EN 60715
Product Tradename		xEffect Accessories
Product Type		Mounting part
Product Sub Type		None
Delivery program		
Type		General switchboard accessory
Model		DIN rail (top hat rail) 35/7.5 mm
Accessory/spare part type		DIN-rail
Technical Data - Mechanical		
Surface finishing		Galvanic/electrolytic zinc plated
Material		Steel
Material thickness		1 mm
Drill hole distance (centrically)		36 mm
Punch shape		Long-slot
Additional information		
Special features		35 x 7.5 mm. Short-circuit strength as PE conductor corresponds to 16 mm <sup>2</sup> copper conductor as defined in IEC/EN 61439-1. Isolation in hole permitted. Supplied in lengths of 2 m.

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Mounting rail (EC001285)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / DIN rail (ecl@ss13-27-40-06-02 [AC0367016])			
Model			DIN rail (top hat rail) 35/7.5 mm
Material			Steel
Surface protection			Galvanic/electrolytic zinc plated
Punch shape			Long-slot
Drill hole distance centrically		mm	36
Material thickness		mm	1
Length		mm	2000
Height		mm	8