

Voltmeter selector switches, T0, 20 A, flush mounting, 2 contact unit(s),  
Contacts: 4, 45 °, maintained, Without 0 (Off) position, Phase/Phase,  
Design number 15922



Part no.                    T0-2-15922/E  
                                  053099

|  |  |  |
|--|--|--|
| General specifications                 |  |  |
| Product name                           |  | Eaton Moeller® series T0 Voltmeter selector switch   |
| Part no.                               |  | T0-2-15922/E   |
| EAN                                    |  | 4015080530992  |
| Product Length/Depth                   |  | 86 millimetre  |
| Product height                         |  | 48 millimetre  |
| Product width                          |  | 48 millimetre  |
| Product weight                         |  | 0.108 kilogram   |
| Certifications                         |  | UL Category Control No.: NLRV<br>UL<br>UL 60947-4-1<br>CE<br>UL File No.: E36332<br>IEC/EN 60947-3<br>CSA File No.: 012528<br>IEC/EN 60204<br>CSA-C22.2 No. 60947-4-1-14<br>VDE 0660<br>CSA Class No.: 3211-05<br>CSA-C22.2 No. 94<br>IEC/EN 60947<br>CSA<br>UL<br>CSA |
| Product Tradename                      |  | T0   |
| Product Type                           |  | Voltmeter selector switch  |
| Product Sub Type                       |  | None   |
| Catalog Notes                          |  | Rated Short-time Withstand Current (Icw) for a time of 1 second  |
| Features & Functions                   |  |  |
| Fitted with:                           |  | Black thumb grip and front plate<br>Control unit   |
| Functions                              |  | Measurement between phases possible  |
| Inscription                            |  | " Phase/Phase "  |
| Number of poles                        |  | 2  |
| Switch function type                   |  | 3 x phase-phase  |
| General information                    |  |  |
| Degree of protection                   |  | NEMA 12<br>IP65  |
| Degree of protection (front side)      |  | IP65   |
| Lifespan, mechanical                   |  | 400,000 Operations   |
| Mounting method                        |  | Flush mounting   |
| Mounting position                      |  | As required  |
| Number of contact units                |  | 2  |
| Operating frequency                    |  | 1200 Operations/h  |
| Overvoltage category                   |  | III  |
| Pollution degree                       |  | 3  |
| Rated impulse withstand voltage (Uimp) |  | 6000 V AC  |
| Safe isolation                         |  | 440 V AC, Between the contacts, According to EN 61140  |
| Safety parameter (EN ISO 13849-1)      |  | B10d values as per EN ISO 13849-1, table C.1   |
| Shock resistance                       |  | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms  |
| Suitable for                           |  | Branch circuits, suitable as motor disconnect, (UL/CSA)  |
| Switching angle                        |  | 45 °   |
| Type                                   |  | Voltmeter selector switch  |
| Climatic environmental conditions      |  |  |

|  |  |   |
|--|--|---|
| Ambient operating temperature - min                                    |  | -25 °C  |
| Ambient operating temperature - max                                    |  | 50 °C   |
| Ambient operating temperature (enclosed) - min                         |  | -25 °C  |
| Ambient operating temperature (enclosed) - max                         |  | 40 °C   |
| Climatic proofing  |  | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78  |
| <b>Terminal capacities</b>   |  |   |
| Terminal capacity (flexible with ferrule)                              |  | 1 x (0.75 - 2.5) mm <sup>2</sup> , ferrules to DIN 46228<br>2 x (0.75 - 2.5) mm <sup>2</sup> , ferrules to DIN 46228                    |
| Terminal capacity (solid/flexible with ferrule AWG)                    |  | 18 - 14   |
| Terminal capacity (solid/stranded)                                     |  | 2 x (1 - 2.5) mm <sup>2</sup><br>1 x (1 - 2.5) mm <sup>2</sup>  |
| Screw size   |  | M3.5, Terminal screw  |
| Tightening torque  |  | 8.8 lb-in, Screw terminals<br>1 Nm, Screw terminals   |
| <b>Electrical rating</b>   |  |   |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)          |  | 100 A   |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)          |  | 110 A   |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3)              |  | 80 A  |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)          |  | 60 A  |
| Rated operational current (Ie)   |  | 8.5 A at AC-3, 690 V star-delta<br>15.6 A at AC-3, 500 V star-delta<br>20 A at AC-3, 230 V star-delta<br>20 A at AC-3, 400 V star-delta |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V            |  | 11.5 A  |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V            |  | 11.5 A  |
| Rated operational current (Ie) at AC-3, 500 V                          |  | 9 A   |
| Rated operational current (Ie) at AC-3, 660 V, 690 V                   |  | 4.9 A   |
| Rated operational current (Ie) at AC-21, 440 V                         |  | 20 A  |
| Rated operational current (Ie) at AC-23A, 230 V                        |  | 13.3 A  |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V                 |  | 13.3 A  |
| Rated operational current (Ie) at AC-23A, 500 V                        |  | 13.3 A  |
| Rated operational current (Ie) at AC-23A, 690 V                        |  | 7.6 A   |
| Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms |  | 10 A  |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms  |  | 10 A  |
| Rated operational current (Ie) at DC-21, 240 V                         |  | 1 A   |
| Rated operational current (Ie) at DC-23A, 24 V                         |  | 10 A  |
| Rated operational current (Ie) at DC-23A, 48 V                         |  | 10 A  |
| Rated operational current (Ie) at DC-23A, 60 V                         |  | 10 A  |
| Rated operational current (Ie) at DC-23A, 120 V                        |  | 5 A   |
| Rated operational current (Ie) at DC-23A, 240 V                        |  | 5 A   |
| Rated operational power at AC-3, 415 V, 50 Hz                          |  | 5.5 kW  |
| Rated operational power at AC-3, 690 V, 50 Hz                          |  | 4 kW  |
| Rated operational power at AC-23A, 220/230 V, 50 Hz                    |  | 3 kW  |
| Rated operational power at AC-23A, 400 V, 50 Hz                        |  | 5.5 kW  |
| Rated operational power at AC-23A, 500 V, 50 Hz                        |  | 7.5 kW  |
| Rated operational power at AC-23A, 690 V, 50 Hz                        |  | 5.5 kW  |
| Rated operational power star-delta at 220/230 V, 50 Hz                 |  | 5.5 kW  |
| Rated operational power star-delta at 380/400 V, 50 Hz                 |  | 7.5 kW  |
| Rated operational power star-delta at 500 V, 50 Hz                     |  | 7.5 kW  |
| Rated operational power star-delta at 690 V, 50 Hz                     |  | 5.5 kW  |
| Rated operational voltage (Ue) at AC - max                             |  | 690 V   |
| Rated uninterrupted current (Iu)                                       |  | 20 A  |
| Uninterrupted current  |  | Rated uninterrupted current Iu is specified for max. cross-section.   |
| <b>Short-circuit rating</b>  |  |   |
| Rated conditional short-circuit current (Iq)                           |  | 6 kA  |
| Rated short-time withstand current (Icw)                               |  | 320 A, Contacts, 1 second   |
| Short-circuit current rating (basic rating)                            |  | 5 kA, SCCR (UL/CSA)   |

|  |  |   |
|--|--|---|
|  |  | 50A, max. Fuse, SCCR (UL/CSA)   |
| Short-circuit current rating (high fault)  |  | 10 kA, SCCR (UL/CSA)<br>20 A, Class J, max. Fuse, SCCR (UL/CSA)   |
| Short-circuit protection rating  |  | 20 A gG/gL, Fuse, Contacts  |
| <b>Switching capacity</b>  |  |   |
| Load rating  |  | 1.3 x I# (with intermittent operation class 12, 60 % duty factor)<br>2 x I# (with intermittent operation class 12, 25 % duty factor)<br>1.6 x I# (with intermittent operation class 12, 40 % duty factor) |
| Number of contacts in series at DC-21A, 240 V                                    |  | 1   |
| Number of contacts in series at DC-23A, 24 V                                     |  | 1   |
| Number of contacts in series at DC-23A, 48 V                                     |  | 2   |
| Number of contacts in series at DC-23A, 60 V                                     |  | 3   |
| Number of contacts in series at DC-23A, 120 V                                    |  | 3   |
| Number of contacts in series at DC-23A, 240 V                                    |  | 5   |
| Switching capacity (main contacts, general use)                                  |  | 16 A, Rated uninterrupted current max. (UL/CSA)   |
| Switching capacity (auxiliary contacts, general use)                             |  | 10A, IU, (UL/CSA)   |
| Switching capacity (auxiliary contacts, pilot duty)                              |  | A600 (UL/CSA)<br>P300 (UL/CSA)  |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)                    |  | 130 A   |
| Voltage per contact pair in series   |  | 60 V  |
| <b>Motor rating</b>  |  |   |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase                                |  | 0.5 HP  |
| Assigned motor power at 200/208 V, 60 Hz, 1-phase                                |  | 1 HP  |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase                                |  | 3 HP  |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase                                |  | 1.5 HP  |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase                                |  | 3 HP  |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase                                |  | 7.5 HP  |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase                                |  | 7.5 HP  |
| <b>Contacts</b>  |  |   |
| Control circuit reliability  |  | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)   |
| Number of contacts   |  | 4   |
| <b>Actuator</b>  |  |   |
| Actuator function  |  | Maintained<br>Without 0 (Off) position  |
| <b>Design verification</b>   |  |   |
| Equipment heat dissipation, current-dependent Pvid                               |  | 0 W   |
| Heat dissipation capacity Pdis   |  | 0 W   |
| Heat dissipation per pole, current-dependent Pvid                                |  | 0.6 W   |
| Rated operational current for specified heat dissipation (In)                    |  | 20 A  |
| Static heat dissipation, non-current-dependent Pvs                               |  | 0 W   |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.  |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.  |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.  |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.  |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | UV resistance only in connection with protective shield.  |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.  |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.  |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.  |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.  |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.  |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.  |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.  |

|  |  |  |  |
|--|--|--|--|
| 10.9.4 Testing of enclosures made of insulating material |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

Technical data ETIM 9.0

|   |  |  |                    |
|---|--|--|--------------------|
| Low-voltage industrial components (EG000017) / Voltmeter selector switch (EC000911)   |  |  |                    |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Volt meter switch (ecl@ss13-27-37-14-11 [AKF068018]) |  |  |                    |
| Measurement between phases possible   |  |  | Yes                |
| Measurement between phase and neutral conductor possible  |  |  | No                 |
| With zero (off) position  |  |  | No                 |
| Device construction   |  |  | Front installation |
| Modular version   |  |  | No                 |
| With control element  |  |  | Yes                |
| Degree of protection (IP)   |  |  | IP65               |
| Degree of protection (NEMA)   |  |  | 12                 |