

Step switches, T3, 32 A, flush mounting, 5 contact unit(s), Contacts: 9, 45 °, maintained, With 0 (Off) position, 0-3, Design number 8281



Powering Business Worldwide™

Part no. T3-5-8281/E
061864

| General specifications | | |
|--|--|---|
| Product name | | Eaton Moeller® series T3 Step switch |
| Part no. | | T3-5-8281/E |
| EAN | | 4015080618645 |
| Product Length/Depth | | 125 millimetre |
| Product height | | 54 millimetre |
| Product width | | 61 millimetre |
| Product weight | | 0.292 kilogram |
| Certifications | | CE CSA UL File No.: E36332 CSA File No.: 012528 IEC/EN 60947 CSA-C22.2 No. 94 UL CSA-C22.2 No. 60947-4-1-14 CSA Class No.: 3211-05 UL Category Control No.: NLRV IEC/EN 60204 UL 60947-4-1 VDE 0660 IEC/EN 60947-3 |
| Product Tradename | | T3 |
| Product Type | | Step switch |
| Product Sub Type | | None |
| Catalog Notes | | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| Features & Functions | | |
| Fitted with: | | Black thumb grip and front plate 0 (off) position |
| Inscription | | 0-3 |
| Number of poles | | Three-pole |
| General information | | |
| Degree of protection | | NEMA 1 NEMA 12 IP65 |
| Degree of protection (front side) | | IP65 NEMA 12 |
| Lifespan, mechanical | | 500,000 Operations |
| Mounting method | | Flush mounting |
| Mounting position | | As required |
| Number of contact units | | 5 |
| Operating frequency | | 1200 Operations/h |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Product category | | Control switches |
| Rated impulse withstand voltage (Uimp) | | 6000 V AC |
| Safe isolation | | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | | Branch circuits, suitable as motor disconnect, (UL/CSA) Front mounting |
| Switching angle | | 45 ° |
| Type | | Step switch |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |

| | |
|--|--|
| Ambient operating temperature - max | 50 °C |
| Ambient operating temperature (enclosed) - min | -25 °C |
| Ambient operating temperature (enclosed) - max | 40 °C |
| Climatic proofing | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Terminal capacities | |
| Terminal capacity (flexible with ferrule) | 1 x (0.75 - 4) mm ² , ferrules to DIN 46228 2 x (0.75 - 4) mm ² , ferrules to DIN 46228 |
| Terminal capacity (solid/flexible with ferrule AWG) | 14 - 10 |
| Terminal capacity (solid/stranded) | 1 x (1 - 6) mm ² 2 x (1 - 6) mm ² |
| Screw size | M4, Terminal screw |
| Tightening torque | 1.6 Nm, Screw terminals 17.7 lb-in, Screw terminals |
| Electrical rating | |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | 240 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | 170 A |
| Rated operating voltage (Ue) at AC - max | 690 V |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 500 V | 23.7 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | 14.7 A |
| Rated operational current (Ie) at AC-21, 440 V | 32 A |
| Rated operational current (Ie) at AC-23A, 230 V | 32 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | 32 A |
| Rated operational current (Ie) at AC-23A, 500 V | 26.4 A |
| Rated operational current (Ie) at AC-23A, 690 V | 17 A |
| Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms | 25 A |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms | 20 A |
| Rated operational current (Ie) at DC-21, 240 V | 1 A |
| Rated operational current (Ie) at DC-23A, 24 V | 25 A |
| Rated operational current (Ie) at DC-23A, 48 V | 25 A |
| Rated operational current (Ie) at DC-23A, 60 V | 25 A |
| Rated operational current (Ie) at DC-23A, 120 V | 12 A |
| Rated operational current (Ie) at DC-23A, 240 V | 5 A |
| Rated operational current (Ie) star-delta at AC-3, 230 V | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 400 V | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 500 V | 32 A |
| Rated operational current (Ie) star-delta at AC-3, 690 V | 25.5 A |
| Rated operational power at AC-3, 415 V, 50 Hz | 11 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | 15 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | 11 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | 7.5 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | 15 kW |
| Rated operational power star-delta at 220/230 V, 50 Hz | 7.5 kW |
| Rated operational power star-delta at 380/400 V, 50 Hz | 15 kW |
| Rated operational power star-delta at 500 V, 50 Hz | 18.5 kW |
| Rated operational power star-delta at 690 V, 50 Hz | 22 kW |
| Rated uninterrupted current (Iu) | 32 A |
| Uninterrupted current | Rated uninterrupted current Iu is specified for max. cross-section. |
| Short-circuit rating | |
| Rated conditional short-circuit current (Iq) | 1 kA |

| | | |
|--|--|---|
| Rated short-time withstand current (I _{cs}) | | 650 A, Contacts, 1 second |
| Short-circuit current rating (basic rating) | | 5 kA, SCCR (UL/CSA) 40A, max. Fuse, SCCR (UL/CSA) |
| Short-circuit current rating (high fault) | | 10 kA, SCCR (UL/CSA) 40 A, Class J, max. Fuse, SCCR (UL/CSA) |
| Short-circuit protection rating | | 35 A gG/gL, Fuse, Contacts |
| Switching capacity | | |
| Load rating | | 1.6 x I _# (with intermittent operation class 12, 40 % duty factor) 1.3 x I _# (with intermittent operation class 12, 60 % duty factor) 2 x I _# (with intermittent operation class 12, 25 % duty factor) |
| Number of contacts in series at DC-21A, 240 V | | 1 |
| Number of contacts in series at DC-23A, 24 V | | 1 |
| Number of contacts in series at DC-23A, 48 V | | 2 |
| Number of contacts in series at DC-23A, 60 V | | 3 |
| Number of contacts in series at DC-23A, 120 V | | 3 |
| Number of contacts in series at DC-23A, 240 V | | 5 |
| Switching capacity (main contacts, general use) | | 25 A, Rated uninterrupted current max. (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | | 10A, IU, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | | A600 (UL/CSA) |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | | 320 A |
| Voltage per contact pair in series | | 24 V |
| Motor rating | | |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | | 1.5 HP |
| Assigned motor power at 200/208 V, 60 Hz, 1-phase | | 3 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | | 7.5 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | | 10 HP |
| Contacts | | |
| Control circuit reliability | | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of contacts | | 9 |
| Actuator | | |
| Actuator function | | With 0 (Off) position Maintained |
| Actuator type | | Toggle |
| Number of switch positions | | 4 |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 1.1 W |
| Rated operational current for specified heat dissipation (I _n) | | 32 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |

| | | |
|--|--|--|
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|--|---|-----------------|
| Low-voltage industrial components (EG000017) / Control switch (EC002611) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Control switch (ecl@ss13-27-37-14-14 [ACN998016]) | | |
| Type of switch | | Level switch |
| Number of poles | | 3 |
| Max. rated operation voltage U _e AC | V | 690 |
| Rated permanent current I _u | A | 32 |
| Number of switch positions | | 4 |
| With zero (off) position | | Yes |
| With retraction in 0-position | | No |
| Device construction | | Built-in device |
| Width in number of modular spacings | | 0 |
| Suitable for floor mounting | | No |
| Suitable for front mounting | | Yes |
| Suitable for distribution board installation | | No |
| Suitable for intermediate mounting | | No |
| Complete device in housing | | No |
| Type of control element | | Toggle |
| Front shield size | | 48x48 mm |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA), front side | | 12 |