

Mounting ring tool

Part no. R16-MS
090297
EL Number 4356339
(Norway)

| General specifications | |
|--|--|
| Product name | Eaton Moeller® series RMQ16 Accessory Mounting ring tool |
| Part no. | R16-MS |
| EAN | 4015080902973 |
| Product Length/Depth | 117 millimetre |
| Product height | 68 millimetre |
| Product width | 76 millimetre |
| Product weight | 0.01 kilogram |
| Certifications | UL/CSA certification not required |
| Product Tradename | RMQ16 |
| Product Type | Accessory |
| Product Sub Type | Mounting ring tool |
| Catalog Notes | For lock nut with bulb extractor |
| General information | |
| Model | Mounting wrench |
| Product category | Accessories |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 60 °C |
| Communication | |
| Connection to SmartWire-DT | No |
| Design verification | |
| Equipment heat dissipation, current-dependent Pvid | 0 W |
| Heat dissipation capacity Pdis | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0 W |
| Rated operational current for specified heat dissipation (In) | 0 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Please enquire |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | Not applicable. |
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |

| | | |
|-------------------------------------|--|--|
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|--|-----------------|
| Low-voltage industrial components (EG000017) / Special tool for control circuit devices (EC002032) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Special tool for command and alarm devices (ec@ss13-27-37-12-04 [AC0045016]) | | |
| Model | | Mounting wrench |