



Bottom/Top coverstrip 75mm long, 35mm blind + 40mm foam gasket, IP20, for 1000mm Sectionwidth, grey



Powering Business Worldwide™

Part no. XLST2J10C

Catalog No. 107682

**EL-Nummer 2465262
(Norway)**

Delivery program

| | | |
|--------------------------------------|--|--|
| Product range | | Control centres XVTL |
| Basic function | | Accessories |
| Product function | | Accessories |
| Accessories | | Bottom plates |
| Single unit/Complete unit | | Accessories |
| Description | | Bottom plates as blanking covers adjustable from 60 - 75 mm Cable bushings < # 50 mm possible when using 2 XSPBA... # 50 - 80 mm cable bushings possible when using an XSPBA... in conjunction with XVTL-BP/JL |
| Function | | for downward separation and for cable entries |
| Material | | Sheet steel 1.5 mm |
| Surface finish | | RAL 7035, light grey |
| Information about equipment supplied | | Including screws |
| Suitable for depth | | 60 -75 |
| Suitable for width | | 1000 |
| Cableway | | < Ø 50 mm |

Technical data ETIM 7.0

| | | | |
|--|--|----|-------------|
| Cabinet enclosures (EG000011) / Component for installation (switchgear cabinet) (EC002620) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Elements for switching cabinet, housing, rack / Component for installation (electrical cabinet) (ecl@ss10.0.1-27-18-28-11 [ACN627011]) | | | |
| Model | | | Floor plate |
| Suitable for enclosure building width | | mm | 1000 |
| Suitable for enclosure building height | | mm | 0 |
| Suitable for enclosure building depth | | mm | 0 |
| Width | | mm | 900 |
| Height | | mm | 20 |
| Depth | | mm | 75 |
| Max. load capacity | | kg | 0 |
| Material | | | Metal |
| Colour | | | Grey |
| RAL-number | | | 7035 |