

Connection element, mechanical, for DILM7-M15



**Part no.** PKZM0-XM12DM  
112118

<b>General specifications</b>	
Product name	Eaton Moeller® series PKZM0 Accessory Connection element
Part no.	PKZM0-XM12DM
EAN	4015081116782
Product Length/Depth	42 millimetre
Product height	63.7 millimetre
Product width	45 millimetre
Product weight	0.033 kilogram
Certifications	CSA File No.: 165628 UL 508 CSA UL IEC/EN 60947-4-1 CSA-C22.2 No. 14 CSA Class No.: 3211-05 UL File No.: E36332 CE UL Category Control No.: NLRV
Product Tradename	PKZM0
Product Type	Accessory
Product Sub Type	Connection element
<b>General information</b>	
Model	Other
Product category	Accessories
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
<b>Design verification</b>	
Equipment heat dissipation, current-dependent P <sub>vid</sub>	1.5 W
Heat dissipation capacity P <sub>diss</sub>	0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>	0.5 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )	15.5 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other