

Mounting rail with support bracket, B=72mm



**Part no.** PKZM0-XMR72  
113912

<b>General specifications</b>		
Product name		Eaton Moeller® series PKZM0 Accessory Mounting rail
Part no.		PKZM0-XMR72
EAN		4015081134205
Product Length/Depth		57 millimetre
Product height		18 millimetre
Product width		72 millimetre
Product weight		0.018 kilogram
Compliances		CE Marked
Certifications		CSA Std. C22.2 No. 14 UL 508 IEC 60947-4-1 CSA Class No.: 3211-37 CE CSA-C22.2 No. 14 CSA File No.: 232140 UL File No.: E300273 IEC/EN 60947-4-1 UL UL Category Control No.: NMTR CSA
Product Tradename		PKZM0
Product Type		Accessory
Product Sub Type		Mounting rail
<b>Features &amp; Functions</b>		
Material		Plastic
<b>General information</b>		
Product category		Accessories
Used with		BBA
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / DIN-rail adapter (EC001024)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Mounting rail adapter (ecl@ss13-27-37-04-19 [AKF017018])		
Type of fastening		DIN rail (top hat rail) 35 mm
Type of DIN-rail adapter		Straight
Material		Plastic