

Function element, for combination with RMQ-Titan operating elements  
M22-..., 2 changeover contact, Front fixing, white

**Part no.** M22-SWD-K22LED-W  
**115978**  
**EL Number** 4355013  
**(Norway)**

<b>General specifications</b>	
Product name	Eaton Moeller® series M22 Function element
Part no.	M22-SWD-K22LED-W
EAN	4015081157181
Product Length/Depth	45 millimetre
Product height	42 millimetre
Product width	17 millimetre
Product weight	0.013 kilogram
Certifications	CSA UL CSA File No.: 2324643 UL Category Control No.: NKCR CSA Class No.: 3211-07 UL File No.: E29184 EN 50178 IEC/EN 61131-2 BV LRS
Product Tradename	M22
Product Type	Function element
Product Sub Type	None
<b>Features &amp; Functions</b>	
Color	White
Electric connection type	Flat plug-in connection
Functions	For combination with RMQ-Titan operating elements M22-... Diagnosis function
<b>General information</b>	
Degree of protection	IP20
Model	Top mounting
Mounting method	Front fastening
Overvoltage category	Not applicable
Pollution degree	2
Product category	SmartWire-DT RMQ connections
<b>Ambient conditions, mechanical</b>	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	80 °C
Environmental conditions	Condensation: prevent with appropriate measures
Relative humidity	5 - 95 % (non-condensing, IEC/EN 60068-2-30)
<b>Electro magnetic compatibility</b>	
Air discharge	8 kV, according to IEC 61131-2, level 3, ESD
Burst impulse	2 kV, Supply cable, according to IEC/EN 61131-2, Level 3

Contact discharge	1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3
Electromagnetic fields	4 kV, according to IEC/EN 61131-2, Level 2, ESD
Radiated RFI	10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) 1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008)
Radio interference class	10 V (IEC/EN 61131-2:2008, Level 3)
<b>Electrical rating</b>	
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V	0 A
<b>Communication</b>	
Addressing	Address set automatically
Connection	SmartWire-DT plug connector SWD4-8SF2-5
Connection to SmartWire-DT	Yes
Connection type	Front fixing SWD: Plug, 8-pole
LED indicator	Status indication of SmartWire-DT network: Green LED Status indication of Switching state: Yellow LED
Station	SmartWire-DT slave, SmartWire-DT network
<b>Contacts</b>	
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	2
Number of contacts (normally open contacts)	2
<b>Design verification</b>	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0.3 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block  
(ec@ss13-27-37-13-02 [AKN342018])

Number of contacts as change-over contact		0
Number of contacts as normally open contact		2
Number of contacts as normally closed contact		2
Number of fault-signal switches		0
Rated operation current $I_e$ at AC-15, 230 V	A	0
Type of electric connection		Flat plug-in connection
Model		Clip-on
Mounting method		Front fastening
Lamp holder		LED not exchangeable