

Connection width extension, 3p, 2 studs, size 3



**Part no. NZM4-XKV95-2KB
119861**

General specifications		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM4-XKV95-2KB
EAN		4015081177127
Product Length/Depth		128 millimetre
Product height		130 millimetre
Product width		120 millimetre
Product weight		3.3 kilogram
Compliances		UL/CSA IEC RoHS conform
Certifications		CSA (Class No. 1432-01) UL (File No. E31593) CE marking CSA certified UL (Category Control Number DIHS) CSA-C22.2 No. 5-09 IEC60947 UL489 UL listed CSA (File No. 22086)
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
Delivery program		
Type		Accessory Connection width extension Terminal
Number of poles		Three-pole
Amperage Rating		1600 A
Special features		Two M12 threaded studs
Frame		NZM4
Suitable for		Copper cable lugs Three-pole
Used with		NZM4, N(S)4
Technical Data - Mechanical		
Special features		Two M12 threaded studs
Technical Data - Mechanical - Terminals		
Terminal capacity (stranded cable)		95 mm ² - 300 mm ² (4x) 500 AWG/kcmil (4x)
Terminal capacity (copper busbar)		10 mm x 80 mm (2x)
Terminal capacity (copper strip)		10 segments of 80 mm x 1 mm (2x)
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Model			Other

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other