



**Mounting set IEC Busbar support SASY for MSW application 4 poles  
WxH=1000x300mm**

**Part no. BPZ-BR/SASY/MSW/H-4/1000**

**Catalog No. 120712**

**EL-Nummer 2460988  
(Norway)**

### Delivery program

|                            |  |    |   |
|----------------------------|--|----|---|
| Mounting type              |  |    | Floor standing distribution board<br>Surface mounted<br>Flush mounted |
| Mounting position          |  |    | horizontal  |
| Device mounting positions  |  |    | vertikal  |
| Number of poles            |  |    | 4 pole  |
| Width                      |  | mm | 1000  |
| Height                     |  | mm | 300   |
| Suitable for width         |  | mm | 1000  |
| Colour                     |  |    | light gray (RAL 7035)   |
| Devices that can be fitted |  |    | SASY  |
| applicable for             |  |    | IEC busbar support<br>MSW assembly configuration                      |
| Assembling quantity        |  |    | for single mounting   |

### Technical data ETIM 7.0

|   |  |    |                |
|---|--|----|----------------|
| Energy distribution systems (EG000015) / Distributor assembly busbars (EC001896)  |  |    |                |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly busbars<br>(ecl@ss10.0.1-27-40-06-10 [AC0383011]) |  |    |                |
| Height  |  | mm | 299            |
| Width   |  | mm | 920            |
| Depth   |  | mm | 63             |
| With cover  |  |    | Yes            |
| Number of poles   |  |    | 4              |
| Busbar distance   |  | mm | 60             |
| Busbar height   |  | mm | 30             |
| Busbar thickness  |  | mm | 5              |
| Max. rated current  |  | A  | 400            |
| Short-circuit breaking capacity (I <sub>cw</sub> )  |  | kA | 0              |
| Busbar position   |  |    | Centre central |