

Through terminals, 500VAC/DC, 63A, 50/60Hz, 1HP



**Part no. ASLTT-63  
131784**

General specifications		
Product name		Eaton Distribution parts
Part no.		ASLTT-63
EAN		5019586148940
Product Length/Depth		80 millimetre
Product height		65.5 millimetre
Product width		17.5 millimetre
Product weight		0.108 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Additional equipment required		Other
Application		Open areas Residential buildings Utility buildings
Assembly width		1
Device fitting		Other
Functions		Other function
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		0
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		690 V
Rated switch current		63 A
Suitable for current of main contact unit - max		0 A
Type		Accessory Leadthrough
Used with		SPMT2PA Accessory Leadthrough
Voltage type		AC

### Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec!@ss13-27-14-35-02 [AKE327018])		
Device fitting		Other
Function		Other
Width in number of modular spacings		1
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	63
Rated voltage	V	690

Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0