

Connection width extension, 4p, 2-hole



**Part no.**                      **NZM3-4-XKV70-2**  
**132673**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM3-4-XKV70-2
EAN		4015081296118
Product Length/Depth		100.2 millimetre
Product height		93.5 millimetre
Product width		161.6 millimetre
Product weight		0.82 kilogram
Compliances		IEC RoHS conform
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
<b>Delivery program</b>		
Type		Accessory Connection width extension Terminal
Number of poles		Four-pole
Amperage Rating		630 A
Special features		Two holes
Frame		NZM3
Suitable for		Four-pole Copper cable lugs
Used with		NZM3-4, PN3-4, N(S)3-4
<b>Technical Data - Mechanical</b>		
Special features		Two holes
<b>Technical Data - Mechanical - Terminals</b>		
Terminal capacity (flexible cable)		300 mm <sup>2</sup> (2x) 500 AWG/kcmil (2x)
Terminal capacity (copper busbar)		10 mm x 50 mm (2x)
Terminal capacity (copper strip)		10 segments of 50 mm x 1 mm (2x)
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss13-27-37-13-05 [ACN990017])		
Suitable for number of poles		4