

## Miniature circuit breaker (MCB), 32 A, 3p, characteristic: B

**Part no.** FAZ-B32/3-NA  
**132728**  
**EL Number** 1691563  
**(Norway)**

| General specifications                                       |  |  |
|--|--|--|
| Product name   |  | Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB  |
| Part no.   |  | FAZ-B32/3-NA   |
| EAN  |  | 4015081296774  |
| Product Length/Depth   |  | 105 millimetre   |
| Product height   |  | 75.5 millimetre  |
| Product width  |  | 53.1 millimetre  |
| Product weight   |  | 0.387 kilogram   |
| Compliances  |  | RoHS conform   |
| Certifications   |  | Specially designed for North America, suitable as BCPD<br>UL (File No. E235139)<br>CSA-C22.2 No. 5-09<br>CE marking<br>UL 489<br>North America (UL listed, CSA certified)<br>IEC 60947-2<br>UL 489, CSA C22.2 No. 5<br>IEC/EN 60947-2<br>UL (Category Control Number DIVQ)<br>CSA (File No. 204453)<br>CSA (Class No. 1432-01)<br>EN45545-2<br>IEC 61373 |
| Product Tradename  |  | xEffect - FAZ-NA, FAZ-RT   |
| Product Type   |  | MCB  |
| Product Sub Type   |  | None   |
| Delivery program   |  |  |
| Application  |  | Feeder circuits, branch circuits<br>Switchgear for export to North America (UL-listed)   |
| Number of poles  |  | Three-pole   |
| Number of poles (total)                                      |  | 3  |
| Number of poles (protected)                                  |  | 3  |
| Tripping characteristic                                      |  | B  |
| Release characteristic                                       |  | B  |
| Amperage Rating  |  | 32 A   |
| Type   |  | FAZ-NA<br>Miniature circuit breaker  |
| Technical Data - Electrical                                  |  |  |
| Voltage type   |  | AC   |
| Voltage rating   |  | 277 V AC / 480 V AC  |
| Voltage rating at DC   |  | 60 V DC  |
| Voltage rating (IEC/EN 60947-2)                              |  | 440 V  |
| Voltage rating (UL)  |  | 480Y/277 V   |
| Rated operational voltage (Ue) - max                         |  | 415 V  |
| Rated insulation voltage (Ui)                                |  | 440 V  |
| Rated impulse withstand voltage (Uimp)                       |  | 4 kV   |
| Frequency rating - min                                       |  | 50 Hz  |
| Frequency rating - max                                       |  | 60 Hz  |
| Rated switching capacity (IEC/EN 60947-2)                    |  | 15 kA  |
| Breaking capacity  |  | 10 kA (UL489)  |
| Rated short-circuit breaking capacity (EN 60898) at 230 V    |  | 0 kA   |
| Rated short-circuit breaking capacity (EN 60898) at 400 V    |  | 0 kA   |
| Rated short-circuit breaking capacity (IEC 60947-2) at 230 V |  | 15 kA  |
| Rated short-circuit breaking capacity (IEC 60947-2) at 400 V |  | 15 kA  |

|  |  |   |
|--|--|---|
| Selectivity class  |  | 3   |
| Lifespan, electrical   |  | 20000 operations  |
| Overvoltage category   |  | III   |
| Pollution degree   |  | 2   |
| Direction of incoming supply   |  | As required   |
| <b>Technical Data - Mechanical</b>   |  |   |
| Frame  |  | 45 mm   |
| Enclosure width  |  | 105 mm  |
| Width in number of modular spacings  |  | 3   |
| Built-in depth   |  | 70.5 mm   |
| Mounting width   |  | 17.7 mm   |
| Mounting width per pole  |  | 17.7 mm   |
| Mounting Method  |  | Top-hat rail IEC/EN 60715   |
| Mounting position  |  | As required   |
| Degree of protection   |  | UL/CSA Type: -<br>IP20 (IEC)<br>IP20<br>IP40 (when fitted)  |
| Terminals (top and bottom)   |  | Twin-purpose terminals  |
| Connectable conductor cross section (solid-core) - min                     |  | 1 mm <sup>2</sup>   |
| Connectable conductor cross section (solid-core) - max                     |  | 25 mm <sup>2</sup>  |
| Connectable conductor cross section (multi-wired) - min                    |  | 1 mm <sup>2</sup>   |
| Connectable conductor cross section (multi-wired) - max                    |  | 25 mm <sup>2</sup>  |
| Terminal protection  |  | Finger and hand touch safe, DGUV VS3, EN 50274  |
| Tightening torque  |  | UL: 2.4 Nm (21 lb-in) for AWG 18 - AWG 12<br>Max. 2.4 Nm<br>UL: 2.8 Nm (25 lb-in) for AWG 10 - AWG 8<br>UL: 4 Nm (36 lb-in) for AWG 6 |
| <b>Design verification as per IEC/EN 61439 - technical data</b>            |  |   |
| Rated operational current for specified heat dissipation (I <sub>n</sub> ) |  | 32 A  |
| Heat dissipation per pole, current-dependent                               |  | 0 W   |
| Equipment heat dissipation, current-dependent                              |  | 10.2 W  |
| Static heat dissipation, non-current-dependent                             |  | 0 W   |
| Heat dissipation capacity  |  | 0 W   |
| Ambient operating temperature - min  |  | -25 °C  |
| Ambient operating temperature - max  |  | 75 °C   |
| <b>Additional information</b>  |  |   |
| Current limiting class   |  | 3   |
| Features   |  | Additional equipment possible   |
| Functions  |  | Current limiting circuit breaker  |
| Special features   |  | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity                             |
| Used with  |  | FAZ-NA<br>Miniature circuit breaker   |

## Technical data ETIM 9.0

|   |    |      |
|---|----|------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)  |    |      |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019]) |    |      |
| Built-in depth  | mm | 70.5 |
| Release characteristic  |    | B    |
| Number of poles (total)   |    | 3    |
| Number of protected poles   |    | 3    |
| Rated current   | A  | 32   |
| Rated voltage   | V  | 415  |
| Rated insulation voltage U <sub>i</sub>   | V  | 440  |
| Rated impulse withstand voltage U <sub>imp</sub>  | kV | 4    |
| Rated short-circuit breaking capacity I <sub>cn</sub> according to EN 60898 at 230 V  | kA | 0    |

|   |                 |          |
|---|-----------------|----------|
| Voltage type  |                 | AC       |
| Rated short-circuit breaking capacity I <sub>cn</sub> according to EN 60898 at 400 V    | kA              | 0        |
| Rated short-circuit breaking capacity I <sub>cu</sub> according to IEC 60947-2 at 230 V | kA              | 15       |
| Rated short-circuit breaking capacity I <sub>cu</sub> according to IEC 60947-2 at 400 V | kA              | 15       |
| Frequency   | Hz              | 50 - 60  |
| Power loss  | W               | 10.5     |
| Current limiting class  |                 | 3        |
| Flush-mounted installation  |                 | No       |
| Concurrently switching neutral conductor  |                 | No       |
| Over voltage category   |                 | 3        |
| Pollution degree  |                 | 2        |
| Additional equipment possible   |                 | Yes      |
| Width in number of modular spacings   |                 | 3        |
| Degree of protection (IP)   |                 | IP20     |
| Ambient temperature during operating  | °C              | -25 - 75 |
| Connectable conductor cross section multi-wired   | mm <sup>2</sup> | 1 - 25   |
| Connectable conductor cross section solid-core  | mm <sup>2</sup> | 1 - 25   |
| Explosion-proof   |                 | No       |