

Soft starter, 24 A, 200 - 480 V AC, Us= 110 - 230 V AC, Frame size FS2



**Part no.** DS7-342SX024N0-N  
**134931**  
**EL Number** 4134272  
**(Norway)**

General specifications		
Product name		Eaton DS7 Soft starter
Part no.		DS7-342SX024N0-N
EAN		4015081317462
Product Length/Depth		118 millimetre
Product height		150 millimetre
Product width		45 millimetre
Product weight		0.4 kilogram
Compliances		Contact Manufacturer
Certifications		CSA-C22.2 No 14-05 CSA File No.: 2511305 UL File No.: E251034 CSA Class No.: 321106 GB 14048.6 CE CSA UL 508 CSA-C22.2 No 0-M91 C-Tick UL CSA22.2-14 IEC/EN 60947-4-2 UkrSEPRO UL CSA
Product Tradename		DS7
Product Type		Soft starter
Product Sub Type		None
Catalog Notes		Ambient Operating Temperature up to 60 at 2% derating per Kelvin temperature rise External Reversing starter solution required Regulator supply: External supply voltage
Features & Functions		
Fitted with:		Internal bypass Internal bypass contacts
Functions		Potential isolation between power and control sections Min. ramp time 1 s - fast switching (semiconductor contactor) Single direction Soft start function Suppression of closing transients Suppression of DC components for motors
General information		
Class		Other
Connection to SmartWire-DT		No
Degree of protection		IP20 NEMA 1
Frame size		FS2
Mains voltage - min		200 V
Mains voltage - max		480 V
Overvoltage category		II
Pollution degree		2
Radio interference class		Class A (EN 55011)
Suitable for		Branch circuits, (UL/CSA)
Type		Soft starter for three-phase loads
Voltage type		AC
Ambient conditions, mechanical		
Mounting position		Vertical
Shock resistance		8 g, 11 ms, Mechanical

Vibration resistance		2M2 to EN 60721-3-2
<b>Climatic environmental conditions</b>		
Altitude		Max. 2000 m Above 1000 m with 1 % derating per 100 m
Ambient operating temperature - min		-5 °C
Ambient operating temperature - max		40 °C
Ambient storage temperature - min		-25 °C
Ambient storage temperature - max		60 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-3
<b>Main conducting paths</b>		
Overload cycle		AC-53a: 3 - 5: 75 - 10
Rated operational current (Ie) at AC-53		24 A
Rated operational voltage (Ue) - min		230 V
Rated operational voltage (Ue) - max		480 V
Short-circuit protection rating		PKM0-25 (+ CL-PKZ0), Type "1" coordination, Main conducting paths 3 x 170M1365, Type „2" coordination (additional with the fuses for coordination type „1"), Main conducting paths
Supply frequency		50/60 Hz, fLN, Main circuit
Voltage rating - max		480 V
<b>Motor rating</b>		
Assigned motor power at 200/208 V, 60 Hz, 3-phase		7.5 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase		7.5 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		15 HP
Rated operational power at 220/230 V, 50 Hz		5.5 kW
Rated operational power at 400 V, 50 Hz		11 kW
<b>Terminal capacities</b>		
Terminal capacity (flexible with ferrule)		2 x (0.5 - 0.75) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables 1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 10) mm <sup>2</sup> , Main cables
Terminal capacity (solid)		2 x (0.5 - 1.0) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 10) mm <sup>2</sup> , Main cables 1 x (0.5 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables
Terminal capacity (solid/stranded AWG)		1 x (21 - 14), Control circuit cables 2 x (21 - 18), Control circuit cables 18 - 6, Main cables
Terminal capacity (stranded)		1 x 16 mm <sup>2</sup> , Main cables 2 x (0.5 - 1.0) mm <sup>2</sup> , Control circuit cables 1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables
Screwdriver size		0.6 x 5.5 mm/1 x 6 mm, Terminal screws, Control circuit cables PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver
Tightening torque		1.2 Nm, Screw terminals, Control circuit cables 3.2 Nm
<b>Control circuit</b>		
Current consumption		50 mA, Control circuit, Regulator supply 1.6 mA, Control circuit, Digital inputs, External 24 V
Drop-out time		350 ms, Control circuit, Digital Inputs, AC operated
Drop-out voltage		AC operated: 0 - 15 V, AC operated
Pick-up time		250 ms at AC
Pick-up voltage		108 - 253 V AC
Rated control supply voltage (Us) at AC, 50 Hz - min		110 V
Rated control supply voltage (Us) at AC, 50 Hz - max		230 V
Rated control supply voltage (Us) at AC, 60 Hz - min		110 V
Rated control supply voltage (Us) at AC, 60 Hz - max		230 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
<b>Input/Output</b>		
Input current		4 mA (at 230 V AC, Digital inputs)
Number of outputs		2 Relay Outputs (TOR, Ready)

Output voltage		250 V AC (relay outputs)
Protection		Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)		110 - 230 V AC 110 - 230 V AC (-15 %/+10 %)
Rated operational current (Ie) at AC-11		1 A
<b>Soft start function</b>		
Application		1-phase motors: No 3-phase motors: Yes Soft starting of three-phase asynchronous motors
Delay time		0 - 30 s, Soft start function, Ramp times
Ramp/run-up time		1 - 30 s
Start voltage		Max. 100 %, Soft start function, Start voltage = turn-off voltage Min. 30 %, Soft start function, Start voltage = turn-off voltage
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		1.1 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		24 A
Static heat dissipation, non-current-dependent Pvs		1.1 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecl@ss13-27-37-09-07 [AC0300016])		
Rated operation current Ie at 40 °C Tu	A	24
Rated operating voltage Ue	V	230 - 480
Rated power three-phase motor, inline, at 230 V	kW	5.5
Rated power three-phase motor, inline, at 400 V	kW	11
Rated power three-phase motor, inside delta, at 230 V	kW	0
Rated power three-phase motor, inside delta, at 400 V	kW	0
Function		Single direction
Internal bypass		Yes
With display		No
Torque control		No

Rated surrounding temperature without derating	°C	40
Rated control supply voltage AC 50 Hz	V	110 - 230
Rated control supply voltage AC 60 Hz	V	110 - 230
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Integrated motor overload protection		No
Release class		Other
Degree of protection (IP)		IP20
Degree of protection (NEMA)		1