

15KBR12

Product name		Eaton Bussmann series medium voltage expulsion fuse
Part no.		15KV 12A REMOVABLE B/HEAD EXPULSION LINK
EAN		5027590435406
Product Length/Depth		225 millimetre
Product height		76 millimetre
Product width		106 millimetre
Product weight		19.24 gram
Compliances		ANSI C37.42
Certifications		Contact Manufacturer
Product Tradename		None
Product Type		Medium voltage expulsion fuse
Product Sub Type		None
Amperage Rating		12 A
Voltage rating		15 kV
Current characteristic type		Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics
Rated frequency - min		50 Hz
Rated frequency - max		60 Hz
Application		Primary side transformer protection, feeder protection, capacitor bank protection
Standard		ANSI
Type of termination		Removable buttonhead

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) (ecl@ss10.0.1-27-14-21-90 [BAB265011])		
Rated current	A	12
Rated voltage	kV	15
Voltage type		AC
Rated frequency	Hz	50 - 60
Release characteristic		K
Type of termination		Removable buttonhead
Standard		ANSI